

Code: GL-402

INDOOR MOTOR UNIT **GL-402**

Net: **71.54 EUR** Gross: **71.54 EUR**

There is a possibility to limit the Pan angle, and built-in the scan function (right - left periodic rotations). The device can be voltage controlled via the SOM-5 controller or by RS-485 interface via the SOT-5 controller with the keyboard controller, eg KT-608.



SPECIFICATION

Vertical rotation range:	$\pm 60^\circ$
Horizontal rotation range:	350°
Vertical rotation speed:	$3^\circ/\text{s}$
Horizontal rotation speed:	$6^\circ/\text{s}$
Maximal load:	5 kg
Power supply:	24 V AC
Power consumption:	6 W
Material:	Aluminum
Operation temp:	$-25^\circ\text{C} \dots 60^\circ\text{C}$
Weight:	3.7 kg
Dimensions:	$\varnothing 196 \times 277 \text{ mm}$
Guarantee:	2 years

PRESENTATION

Top view (camera or housing mounting):



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Motor unit control connector (6-wire cable):



1. Auto mode
 2. COM
 3. down
 4. up
 5. right
 6. left
- In the kit:



Examples of control the motor unit:



1) Motor unit
2) Voltage control
Different motor units dimensions comparison:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------