

Code: PFS3006-4ET-36

## SWITCH POE **PFS3006-4ET-36** 4-PORT DAHUA

Net: **44.03 EUR** Gross: **44.03 EUR**

Due to reliability and ensuring high quality of transmission, the PFS3006-4ET-36 10/100 Mb/s 4-port PoE desktop type switch is perfect solution for expanding home or office network. Four ports support Power over Ethernet (PoE) function.

**Attention!** When the Extend function is enabled the PoE range increases up to 250m and the transmission speed reduces to 10 Mb/s.



### SPECIFICATION

|                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|-----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| LAN ports:            | <ul style="list-style-type: none"><li>• 2 x RJ45 10/100 Base-TX - Uplink,</li><li>• 4 x RJ45 10/100 Base-TX ( 4 x PoE (802.3af/at) )</li></ul>                                                                                                                                                                                                                                                                                                                                                                        |
| Standards:            | IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3af, IEEE 802.3at                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Management:           | —                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| LED diodes:           | Power, Link/Act, PoE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Transmission speed:   | 10 / 100 Mbps : 2 LAN ports + 4 LAN & PoE ports                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Maximal output power: | 30 W / port PoE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Maximal total power:  | 36 W                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| MAC addresses table:  | 2k                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Operation modes:      | <ul style="list-style-type: none"><li>• Extend On : 250 m, 10 Mbps</li><li>• Extend Off : 100 m, 100 Mbps</li></ul>                                                                                                                                                                                                                                                                                                                                                                                                   |
| Main features:        | <ul style="list-style-type: none"><li>• PoE power mode : The device supports 8-pin power supply</li><li>• EXTEND mode - ports PoE1, PoE2, PoE3, PoE4 support transmission up to 250 m</li><li>• Watchdog PoE / PD Alive mode - monitoring of the ports that power PoE devices and automatic restart by cutting off the power supply when an unresponsive device is detected</li><li>• protection against lightning discharges and voltage differences and strokes between devices</li><li>• Kensington Lock</li></ul> |
| Certificates:         | CE, FCC                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Power supply:         | 100 V ... 240 V AC                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Operation temp:       | -10 °C ... 55 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Weight:               | 0.56 kg                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Dimensions:           | 194 x 108 x 35 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Manufacturer / Brand: | DAHUA                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Guarantee:            | <b>3 years</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |

### PRESENTATION



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

Front view:



- 1. LAN: Uplink
- 2. LAN + PoE

Rear view:



In the kit:



PACKAGE

|                                  |                    |
|----------------------------------|--------------------|
| Dimensions (L x W x H): 0x0x0 mm | Gross Weight: 0 kg |
|----------------------------------|--------------------|