

Code: DS-3E1309P-EI

SWITCH POE **DS-3E1309P-EI** 8-PORT Hikvision

Net: **349.00 PLN** Gross: **349.00 PLN**

The DS-3E1309P-EI PoE Switch ensuring smooth network transmission at the speed 10 / 100 Mbps.

8 ports support Power over Ethernet (PoE) function. When the Extend function is enabled the PoE range increases up to 300m and the transmission speed reduces to 10 Mb/s.



SPECIFICATION

LAN ports:	• 8 x RJ45 10/100 Base-TX (8 x PoE (802.3af/at)), • 1 x RJ45 10/100/1000 Base-TX - Uplink
Transmission speed:	• 10 / 100 Mbps - 8 LAN & PoE ports, • 10 / 100 / 1000 Mbps - 1 Port Uplink
Maximal output power:	30 W / port PoE 802.3af/at - 1 ... 8 ports
Maximal total power:	110 W
MAC addresses table:	16k
Management:	✓
Operation modes:	Extend On : 300 m, 10 Mbps
LED diodes:	Power, Link/Act, PoE, PoE Max, G1 - Uplink
Main features:	• The device supports 8-pin power supply - wires : 1-2(-), 3-6(+), 4-5(+), 7-8(-) • Endspan mode support - wires : 1-2(-), 3-6(+) • Midspan mode support - wires : 4-5(+), 7-8(-) • Watchdog PoE - 1 ... 8 ports • The device has the ability to work with the Hik-Connect application for mobile devices • View topology and network status • Data Flow Control • Alarm notifications • Remote update of software • System logs • Possibility to mount to the wall
Certificates:	CE, FCC, RoHS
Protections:	Overvoltage 6 kV - PoE ports
Housing:	Desktop, Metal
Power supply:	48 V DC / 2.5 A (power adapter included)
Power consumption:	max. 120 W
Operation temp:	0 °C ... 40 °C
Weight:	0.364 kg
Dimensions:	170 x 93 x 28 mm
Manufacturer / Brand:	Hikvision

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

SAP Code:	301801788
Guarantee:	3 years

PRESENTATION

Front panel:



Rear panel:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------