

Code: DH-LR2110-8ET-120

INDUSTRIAL POE/EPOE SWITCH **DH-LR2110-8ET-120** 10-PORT + SFP DAHUA

Net: **263.93 EUR** Gross: **263.93 EUR**

The DH-LR2110-8ET-120 PoE Switch is an industrial type device enabling fluent network transmission at rates 10 / 100 / 1000 Mbps. Devices of this type can be used in installations realized in industrial facilities in harsh environmental conditions like high or low temperature.

Attention! The SFP port requires the SFP module, which is available in our offer.

The device is equipped with ePoE technology which enables transmission up to 800 m at a speed of 10 Mb/s or 300 m at a speed of 100 Mb/s via cat. 5e twisted-pair.



SPECIFICATION

LAN ports:	<ul style="list-style-type: none">• 1 x port SFP 1000 Base-X - Uplink,• 1 x RJ45 10/100/1000 Base-T - Uplink,• 6 x RJ45 10/100 Base-T + ePoE / PoE (802.3af/at) - Color green,• 2 x RJ45 10/100 Base-T + Hi-PoE / ePoE / PoE (802.3af/at) - Color orange
Transmission speed:	<ul style="list-style-type: none">• 10 / 100 Mbps - 6 LAN & PoE ports,• 10 / 100 / 1000 Mbps - 1 Port LAN - Uplink,• 1000 Mbps - 1 SFP ports - Uplink
Maximal output power:	<ul style="list-style-type: none">• 30 W / port PoE @ PoE (802.3af/at) or ePoE,• 60 W @ High PoE
Maximal total power:	120 W
MAC addresses table:	8k - Auto update of MAC addresses table
Transmission method:	Store and Forward
Main features:	<ul style="list-style-type: none">• Auto-learning and Auto-aging functions support for MAC addresses• Data Flow Control• protection against lightning discharges and voltage differences and strokes between devices• Industrial wide temperature design.
LED diodes:	Power, Link/Act
Power supply:	48 V DC ... 57 V DC (power adapter included)
Operation temp:	-30 °C ... 65 °C
Assembly:	DIN rail (TS-35)

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Weight:	0.6 kg
Dimensions:	150 x 100 x 42 mm
Manufacturer / Brand:	DAHUA
Guarantee:	3 years

PRESENTATION

Front panel:



Power connector:



Mounting side view:



Diagrams of typical installations:

- 1.
- 2.
- 3.
- 4.
- 5.
- 6.

In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------