

Code: ARCHER-T2U

WLAN USB ADAPTER **ARCHER-T2U** 150 Mbps @ 2.4 GHz, 433 Mbps @ 5 GHz TP-LINK

Net: **62.19 PLN** Gross: **62.19 PLN**

Wireless card is practical wireless adapter for use in WiFi networks. The adapter/card is connected to USB port, so it is well suited for portable computers. Enhanced encryption capabilities allow to protect the connections against unauthorized access. Configuration of the card is very easy. The included software enables the user to monitor operation and transmission parameters. It can also operate in roaming between Access Points in Infrastructure mode.



SPECIFICATION

| | |
|--------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Supported standards: | IEEE 802.11 b/g/n @ 2.4 GHz, IEEE 802.11 a/n/ac @ 5 GHz |
| WiFi chipset: | Atheros |
| Supported transmission speeds: | 150 Mbps @ 2.4 GHz , 433 Mbps @ 5 GHz |
| Operation modes: | Ad-Hoc, Infrastructure |
| Modulation: | DBPSK / DQPSK / CCK / OFDM / 16-QAM / 64-QAM |
| Antenna type: | Indoor |
| Interface: | USB |
| Frequency range: | <ul style="list-style-type: none">• 2.4 GHz• 5 GHz |
| Receiver sensitivity: | 5 GHz <ul style="list-style-type: none">• 11a 6M : -94 dBm• 11a 54M : -78 dBm• 11n HT20 MCS0 : -94 dBm• 11n HT20 MCS7 : -77 dBm• 11n HT40 MCS0 : -92 dBm• 11n HT40 MCS7 : -74 dBm• 11ac VHT80 MCS0 : -89 dBm• 11ac VHT80 MCS9 : -64 dBm 2.4 GHz <ul style="list-style-type: none">• 11b 1M : -99 dBm• 11b 11M : -91 dBm• 11g 6M : -94 dBm• 11g 54M : -77 dBm• 11n HT20 MCS0 : -95 dBm• 11n HT20 MCS7 : -76 dBm• 11n HT40 MCS0 : -92 dBm• 11n HT40 MCS7 : -73 dBm |
| Security measures: | WEP 64/128-bit, WPA-PSK/WPA2-PSK, 802.1x Radius |
| Included drivers: | Windows, Mac OS X, Linux |
| Certificates: | FCC, CE, RoHS |

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

| | |
|-----------------------|----------------|
| Operation temp: | 0 °C ... 40 °C |
| Weight: | 0.006 kg |
| Dimensions: | 41 x 20 x 9 mm |
| Manufacturer / Brand: | TP-LINK |
| Guarantee: | 3 years |

PRESENTATION





PACKAGE

| | |
|----------------------------------|--------------------|
| Dimensions (L x W x H): 0x0x0 mm | Gross Weight: 0 kg |
|----------------------------------|--------------------|