

Code: PTF-51-EXT/POE/MICRO

OVERVOLTAGE LIMITER **PTF-51-EXT/POE/MICRO** EWIMAR

Net: 132.74 PLN Gross: 132.74 PLN

The PTF-51-EXT/POE/MICRO device is designed to overvoltage protection of the CCTV systems connected to the Ethernet 10/100 Mb/s network and remotely powered in PoE+ technology. The PoE+ technology allows to power the devices with increased power consumption, such as Speed Dome HD cameras.

At the same time protects the data transmission line and power path. Using the shielded RJ-45 sockets and FTP cable you can ensure shield continuity. The condition of correct protection is connecting the PTF-51-EXT/POE/MICRO device to the proper grounding or PE wire.



SPECIFICATION

Number of channels:	1
Sockets type:	(RJ45) 10/100 Mb FTP cat. 6
Nominal voltage (line-ground):	90 V DC
Maximal voltage line-PG:	110 V DC
Voltage protection level line-PG:	≤ 600 V
Nominal discharge current (line-PG):	100 A - 8/20 μs
Nominal voltage (line-line):	<ul style="list-style-type: none">• 3.3 V DC - data line• 57 V DC - PoE
Maximal voltage (line-line):	<ul style="list-style-type: none">• 3.5 V DC - data line• 64 V DC - PoE
Protected wires:	1-2, 3-6 - data line
Protected pairs of wires:	(1+2)-(3+6), (4+5)-(7+8) - PoE
Connectors type:	<ul style="list-style-type: none">• RJ-45 shielded socket• RJ45 (8P8C) plug on the cable
Length of grounding cable:	0.29 m
Housing:	Plastic
Weight:	0.05 kg
Dimensions:	57 x 31 x 27 mm
Manufacturer / Brand:	EWIMAR

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Guarantee:

2 years

PRESENTATION

Device connectors:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm

Gross Weight: 0 kg