

Code: AXON-VIDEO-IP

OVERVOLTAGE LIMITER AXON-VIDEO-IP

Net: 107.45 PLN Gross: 107.45 PLN

Device is designed to overvoltage protection of devices connected to the Ethernet 10/100/1000 Mb/s networks. It allows to protect all 4 pairs of UTP cable carrying away the discharge current to the ground.



SPECIFICATION

Rated voltage:	5 V
Maximal voltage:	6 V
Voltage protection level (line-line):	≤ 40 V
Voltage protection level line-PG:	≤ 600 V
Nominal discharge current (line-line):	100 A (8/20 μ s)
Nominal discharge current (line-PG):	100 A (8/20 μ s)
Maximal discharge current (line-line):	135 A (8/20 μ s)
Maximal discharge current (line-PG):	135 A (8/20 μ s)
Capacity:	< 20 pF
Protected pairs of wires:	1-2, 3-6, 4-5, 7-8
Sockets types:	RJ45 (8P8C)
Dimensions:	66 x 60 x 30 mm
Weight:	0.05 kg
Guarantee:	2 years

PRESENTATION

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Connectors:



In the kit:

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------