

Code: BCS-CVR0801E-II

HYBRID DVR BCS-CVR0801E-II STANDARD: HD-CVI, TCP/IP, 8 CHANNELSNet: **140.64 EUR** Gross: **140.64 EUR**

Hybrid DVR working in IP and HD-CVI - High Definition Composite Video Interface standards.

The HD-CVI interface allows to transmission of analog, composite video signal via coaxial cable. Via single coaxial cable can be transmitted three signals: video, audio and control. It enables the transmission of HD resolution images for even 500 m distance with keeping the low costs of the installation. During transmission there are no delays and is maintained the original, high quality image.

**SPECIFICATION**

Standard:	HD-CVI, TCP/IP
Maximal total frame rate:	<ul style="list-style-type: none"> • HD-CVI : 50 fps @ 1920 x 1080 px, 100 fps @ 1280 x 720 px, 200 fps @ 960 x 576 px, 200 fps @ 720 x 576 px • IP : 24 fps @ 1080p
Recording speed adjustment:	1 ... 6 fps @ 1920 x 1080 1 ... 12 fps @ 1280 x 720 1 ... 25 fps @ 960 x 576 1 ... 25 fps @ 704 x 576 1 ... 25 fps @ 352 x 288 for each channel
Supported resolutions:	8 x HD-CVI @ 720p / 1080p or 2 x IP @ 1080p
Video inputs:	8 pcs BNC, HD-CVI
Video outputs:	1 pcs HDMI 1 pcs VGA
Audio inputs:	—
Audio outputs:	—
Image compression method:	H.264
Number of compression levels:	4
Image records resolutions:	1920 x 1080 1280 x 720 960 x 576 704 x 576 352 x 288
Recording modes:	Manual, Motion Detection, Schedule
Supported hard drives:	1 x 4 TB SATA
External storage devices backup:	Save single frames and whole records from DVR drive to the USB drive
Searching and playback the records:	Records searching: by time + timeline with record type. Playback: forward, fast, slow, step Advanced searching (to the one second accuracy)
Network functions:	Network Client Software and IE browser: live view, playback and backup of the records, partial configuration of the recorder parameters
Mobile phones support:	Iphone and Android applications

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
 POL; 60-713 Poznań; Graniczna 10
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Alarm inputs / outputs:	—
PTZ control:	—
Motion Detection:	Split the screen into zones 22 x 18 motion zones Very good sensitivity after motion detection records detected channels only
Mouse support:	✓
Power supply:	12 V DC / 2 A (power adapter included)
Weight:	0.585 kg
Dimensions:	211 x 205 x 43 mm
Supported languages:	English, Polish
Country of origin:	China
Guarantee:	2 years
Manufacturer / Brand:	BCS

PRESENTATION

Top view:



Rear view:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

