

Code: FLEX-H1-8M8F

AHD, PAL, TCP/IP DVR **FLEX-H1-8M8F** 8 CHANNELS

Net: **155.59 EUR** Gross: **155.59 EUR**

The FLEX-H1-8M8F digital recorder with AHD (Analog High Definition) and PAL interface is a professional device applicable in surveillance systems. The AHD interface allows to transmission of analog video signal via coaxial cable in 720p resolution. The menu options layout has been designed for all users, even beginners can easy navigate and change parameters in DVR settings without any problem.



SPECIFICATION

Standard:	AHD, PAL, TCP/IP
Video inputs:	8 pcs BNC - AHD, CVBS
Video outputs:	1 pcs HDMI 1 pcs VGA
Audio inputs:	4 pcs CINCH
Audio outputs:	1 pcs CINCH
Image compression method:	H.264
Number of compression levels:	6
Image records resolutions:	AHD-M (1280 x 720) PAL (960 x 576) PAL (704 x 576) PAL (352 x 288) IP (1920 x 1080)
Maximal total frame rate:	AHD : 200 fps @ 1280 x 720 px, AHD, PAL : 200 fps @ 960 x 576 px, PAL : 200 fps @ 704 x 576 px, PAL : 200 fps @ 352 x 288 px, IP : 200 fps @ 1920 x 1080 px
Recording speed adjustment:	1 ... 12 fps @ 1280 x 720 px, It covers the following operation modes : AHD, IP 1 ... 25 fps @ 1280 x 720 px, It covers the following operation modes : AHD, PAL 1 ... 25 fps @ 960 x 576 px - PAL 1 ... 25 fps @ 704 x 573 px - PAL 1 ... 25 fps @ 352 x 288 px - PAL for each channel
Operation modes:	<ul style="list-style-type: none">• 8 x AHD-M• 8 x PAL• 8 x AHD-M + 8 x IP 1080p• 8 x PAL + 8 x IP 1080p• 4 x AHD-M + 4 x PAL + 8 x IP 1080p• 4 x AHD-M + 4 x PAL
Recording modes:	Manual, Sensor, Motion detection, Schedule
Supported hard drives:	1 x 4 TB SATA
External storage devices backup:	Records backup at (.avi) format to USB (pendrive)
Searching and playback the records:	Records searching: by time and events type. Records playback: forward, backward, fast, slow

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Network functions:	Network Client software or IE browser: playback, DVR settings, files download, records searching
Mobile phones support:	Port 5053 <ul style="list-style-type: none"> • Android: Free application MEye • iOS (iPhone): Free application Meye • Windows Phone: Free application Meye Access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application Goolink • iOS (iPhone): Free application Goolink
Alarm inputs / outputs:	4 / 1
PTZ control:	RS-485 - PELCO-D/P
Motion Detection:	Split the screen into zones : 22 x 18 motion zones
Mouse support:	✓
IR remote controller in the set:	✓
Power supply:	12 V DC / 3 A (power adapter included)
Color:	Black
Weight:	1.07 kg
Dimensions:	300 x 221 x 52 mm
Supported languages:	English, Polish
Country of origin:	China
Guarantee:	2 years

PRESENTATION

Front view:



Rear view:



In the kit:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



OUR OPINIONS



- To provide the connection from Internet (WAN) to a DVR connected to the LAN, you should forward on router the following ports: 80, 554, 5050, 5051, 5052, 5053.

PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------