

Code: IVP-02C7

WIRELESS VIDEO DOORPHONE IVP-02C7 Wi-Fi / IP

Net: 449.00 PLN Gross: 449.00 PLN



The Wi-Fi / IP Video Doorphone allows to remote control of the electromagnetic lock using smartphone or tablet. The device transmits an image and operates as intercom system with selected mobile device, and also records the data to the smartphone / tablet.

The function of the monitor with the possibility of opening the door, it may only have a smartphone or tablet, so we decide where currently we have a monitor with a preview of the person pressed a doorbell and to answer the call we do not have to approach the hanging somewhere in the distance monitor.

SPECIFICATION

DOOR STATION:	
Sensor:	1/3 " CMOS
Resolution:	<ul style="list-style-type: none">• 1280 x 720 px• 640 x 360 px
Camera view angle:	110 °
IR illuminator:	—
LED illuminator:	White light (LED) illuminator built-in
PIR detector:	—
Video output:	—
proximity reader built-in:	—
Wireless transmission range:	The range limited only by the availability of the Wi-Fi network
Wi-Fi standard:	IEEE 802.11b / IEEE 802.11g / IEEE 802.11n
Network interface:	<ul style="list-style-type: none">• Ethernet• Wi-Fi
Mobile phones support:	Android, iOS (iPhone, iPad) Android: Free application ControlCam (Eura Video IP) iOS (iPhone): Free application ControlCam (Eura Video IP)
Video format:	H.264
Supported audio formats:	G.711, G.726

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Main features:	<ul style="list-style-type: none"> • IE browser: live view, device configuration, Motion Detection, • Events recording to the smartphone / tablet - Video, still images, • Bidirectional communication, • Full support via network : WiFi / LAN, • Door lock (strike) - 2-wire cable installation, • Remote unlocking of door strike, • Multiple users support from anywhere, • Permanent backlight of name field and call button, • Ability to connect normally open button to leave the property and an electronic chime ,
Mount:	Surface-mounted
Power supply:	12 V DC / 1 A (power adapter included)
Power consumption:	2 W (Standby mode) / 5 W (operation)
Relay contacts load:	max. 48 V DC / 3 A
Operation temp:	-18 °C ... 45 °C
Housing:	Aluminum, Protects against weather conditions
Color:	Silver
"Index of Protection":	IP55
Weight:	0.578 kg
Dimensions:	112 x 136 x 52 mm
Supported languages:	English, Polish
Manufacturer / Brand:	EURA
Guarantee:	2 years

PRESENTATION

Side view:




Connectors:



Rear view:



Schematic diagram (principle of operation):



1. Door Station - activated by pressing a doorbell button
 2. Door lock (strike)
 3. The device communicates via Wi-Fi or LAN
 4. Router WiFi
 5. Mobile network 3G-4G
 6. The device transmits an image and operates as intercom system with selected mobile device, and also records the data to the smartphone / tablet
- A person in the house sees the image from the camera and hears sounds after starts the application on tablet or smartphone
- In the kit:



OUR OPINIONS



- Very easy installation.



- No indoor panel.

PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------