

Code: APTI-XB0401-S33

AHD, HD-CVI, HD-TVI, CVBS, TCP/IP DVR **APTI-XB0401-S33** 4 CHANNELS

Net: **203.28 PLN** Gross: **203.28 PLN**

The APTI-XB0401-S33 digital recorder with AHD (Analog High Definition), HD-CVI (High Definition Composite Video Interface), HD-TVI (High Definition Transport Video Interface), TCP/IP and CVBS interface is a professional device applicable in surveillance systems.

The menu options layout has been designed for all users, even beginners can easy navigate and change parameters in DVR settings without any problem.



SPECIFICATION

Standard:	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP
Video inputs:	4 pcs BNC
Video outputs:	• 1 pcs HDMI • 1 pcs VGA
Audio inputs:	1 pcs CINCH
Audio outputs:	1 pcs CINCH
Image compression method:	H.265+ / H.265 / H.264+ / H.264
Image records resolutions:	• AHD / HD-TVI : 5M-N - 1296 x 1944 px, 4M-N - 1280 x 1440 px, 3M-N - 1024 x 1536 px, 1080N - 960 x 1080 px, 720p - 1280 x 720 px, • HD-CVI : 4M-N - 1280 x 1440 px, 1080N 960 x 1080 px, 720p 1280 x 720 px, • CVBS : 960H - 960 x 576 px, • IP : max. 5 Mpx - 2592 x 1944 px
Recording speed adjustment:	5 Mpx IP @ 1 ... 25 fps 5M-N @ 1 ... 8 fps 4M-N @ 1 ... 15 fps 3M-N @ 1 ... 18 fps 1080N @ 1 ... 18 fps 720p @ 1 ... 20 fps 960H @ 1 ... 25 fps for each channel
Operation modes:	• 4 x AHD / HD-CVI / HD-TVI / CVBS • 2 x AHD / HD-CVI / HD-TVI / CVBS + 4 x IP • 9 x IP All modes allow for any combination of the AHD, HD-CVI, HD-TVI, CVBS cameras
Recording modes:	Motion Detection, Schedule
Supported hard drives:	1 x 8 TB SATA

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

External storage devices backup:	Records backup at (.avi) format to USB (pendrive)
Searching and playback the records:	Records searching: timeline or file list. Playback: forward, backward, fast, slow. Records playback from max. 4 channels in the same time
Network functions:	• Network Client Software (iVMS320): live view, playback and backup of the records • IE browser: live view, playback and backup of the records and configuration of the recorder parameters
Mobile phones support:	Port no.: 6000 or access by a cloud (P2P) • Android: Free application BitVision , Android: Free application iVMS320 • iOS (iPhone): Free application BitVision , iOS: Free application iVMS320
Default IP address:	192.168.1.88
Default admin user / password:	admin / 12345
Web browser access ports:	80, 5000, 554
PC client access ports:	80, 5000, 554
Mobile client access ports:	80, 5000, 6000
Alarm inputs / outputs:	—
PTZ control:	RS-485 interface : Pelco-D, Pelco-P
Motion Detection:	Split the screen into zones : 22 x 18 motion zones
USB:	2 pcs USB 2.0
Mouse support:	✓
IR remote controller in the set:	—
Power supply:	12 V DC / 2 A (power adapter included)
Color:	Black
Weight:	0.69 kg
Dimensions:	260 x 226 x 46 mm
Supported languages:	Polish, English, Bulgarian, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Russian, Turkish, Hungarian, Italian
Country of origin:	China
Manufacturer / Brand:	APTI
Guarantee:	2 years

PRESENTATION

Front view:



Rear view:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
 POL; 60-713 Poznań; Graniczna 10
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



See how to mount a hard disk drive and configure the recorder:

:

In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------