

Code: DS-7216HQHI-K2

AHD, HD-CVI, HD-TVI, CVBS, TCP/IP DVR **DS-7216HQHI-K2** 16 CHANNELS

Hikvision

Net: **1 540.00 PLN** Gross: **1 540.00 PLN**

The DS-7216HQHI-K2 digital recorder with AHD (Analog High Definition) / HD-TVI (High Definition Transport Video Interface), IP - Hikvision and PAL interface is a professional device applicable in surveillance systems. It facilitates TCP/IP monitoring and remote programming of control panels via the Internet.

The menu options layout has been designed for all users, even beginners can easy navigate and change parameters in DVR settings without any problem.



SPECIFICATION

| | |
|-------------------------------|---|
| Standard: | AHD, HD-CVI, HD-TVI, PAL, TCP/IP |
| Video inputs: | 16 pcs BNC - AHD / HD-CVI / HD-TVI / PAL |
| Video outputs: | 1 pcs HDMI - 4K 1 pcs VGA 1 pcs CVBS - BNC socket |
| Audio inputs: | 1 pcs CINCH |
| Audio outputs: | 1 pcs CINCH |
| Image compression method: | H.265 / H.265+ / H.264 / H.264+ |
| Number of compression levels: | 6 |
| Image records resolutions: | <ul style="list-style-type: none">• HD-TVI : 3.0 Mpx - 1920 x 1536, Channels 1 / 2 / 3 / 4 ,• AHD / HD-CVI / HD-TVI : 4M-N - 1280 x 1440 , 1080p - 1920 x 1080 , 1080N - 960 x 1080 , 720p - 1280 x 720 ,• CVBS : 960H - 960 x 576 , D1 - 704 x 576 ,• IP : max. 6 Mpx - 3072 x 2048 |
| Recording speed adjustment: | 6 Mpx IP @ 1 ... 25 fps IP 4M-N @ 1 ... 15 fps 3 Mpx @ 1 ... 15 fps 1080p @ 1 ... 15 fps 1080N @ 1 ... 25 fps 720p @ 1 ... 25 fps 960H @ 1 ... 25 fps for each channel |
| Operation modes: | Firmware V4.20.000, Buiid 181107 • 16 x HD-TVI / AHD / HD-CVI / PAL / IP + 2 x IP |
| Recording modes: | Manual, Motion Detection, Schedule |
| Supported hard drives: | 2 x 10 TB SATA |

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

| | |
|-------------------------------------|---|
| External storage devices backup: | Backup to USB drive (pendrive, external drive) |
| Searching and playback the records: | Records searching: timeline or file list. Playback: forward, fast, slow. Playback max. 16 cameras in the same time |
| Network interface: | 1 x RJ-45 - 10/100/1000 Base-T |
| Bitrate: | 32 ... 6144 kbps |
| Network functions: | Network Client Software and IE browser: live view, playback and backup of the records, partial configuration of the recorder parameters |
| Network protocols: | TCP/IP, PPPoE, DHCP, Hik Cloud P2P, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP, HTTPS, ONVIF |
| Mobile phones support: | Port no.: 8000 or access by a cloud (P2P) Android: Free application iVMS-4500 iOS (iPhone): Free application iVMS-4500 |
| Default IP address: | DHCP or 192.168.1.64 |
| Default admin user / password: | admin / - |
| Web browser access ports: | 80 |
| PC client access ports: | 554 RTSP, 8000 |
| Mobile client access ports: | 8000 |
| Port ONVIF: | 80 |
| RTSP URL: | <ul style="list-style-type: none"> • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no01/ - Main stream • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no02/ - Sub stream |
| Alarm inputs / outputs: | — |
| PTZ control: | RS-485 PELCO-D/P Control compatible with coax HD-TVI Hikvision |
| Motion Detection: | Split the screen into zones : 22 x 18 motion zones |
| Main features: | Intelligent image analysis : intrusion, crossing the line (tripwire), scene changing |
| Mouse support: | ✓ |
| IR remote controller in the set: | — |
| Power supply: | 12 V DC / 5 A (power adapter included) |
| Color: | Black |
| Weight: | 1.91 kg |
| Dimensions: | 380 x 320 x 52 mm |
| Supported languages: | English, Bulgarian, Croatian, Czech, Danish, Estonian, Greek, Spanish, Dutch, German, Norwegian, Polish, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian |
| Manufacturer / Brand: | Hikvision |
| SAP Code: | 300219538 |
| Guarantee: | 3 years |

PRESENTATION

Front panel:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

