

Code: DH-HAC-HDBW2221EP-03

# HD-CVI, PAL VANDALPROOF CAMERA **DH-HAC-HDBW2221EP-03** 60B - 1080p 3.6 mm DAHUA

Net: **93.27 EUR** Gross: **93.27 EUR**

Megapixel camera with 1/2.7" CMOS sensor and HD-CVI (High Definition Composite Video Interface) / PAL. The HD-CVI interface allows to transmission of analog, composite video signal via coaxial cable. It enables the transmission of HD resolution images for even 500 m distance with keeping the low costs of the installation. During transmission there are no delays and is maintained the original, high quality image.



## SPECIFICATION

Standard:	HD-CVI, PAL
Sensor:	1/2.7 " Progressive Scan CMOS
Matrix size:	2.1 Mpx
Resolution:	1920 x 1080 - 1080p 1280 x 720 - 720p 960 x 576 - 960H, PAL
Lens:	3.6 mm
View angle:	90 °
S/N ratio:	> 65 dB
IR illuminator support:	ICR - Movable InfraRed filter
Range of IR illumination:	30 m
IR illuminator power adjustment:	Automatic
Main features:	<ul style="list-style-type: none"><li>• WDR - 120 dB - Wide Dynamic Range</li><li>• 2D-DNR / 3D-DNR - Digital Noise Reduction</li><li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li><li>• ICR - Movable InfraRed filter</li><li>• BLC - Back Light Compensation</li><li>• AGC - Automatic Gain Control</li><li>• Motion Detection - max. 4 zones</li><li>• Privacy zones - max. 8</li><li>• Mirror - Mirror image</li><li>• Auto White Balance</li></ul>
Video output:	HD-CVI, PAL - 1 Vpp / 75 Ω
OSD menu:	OSD menu available via DAHUA recorder

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

Power supply:	12 V DC / 460 mA
Power consumption:	≤ 5.5 W
Housing:	Dome, Metal
Color:	White
Vandal-proof:	IK10
"Index of Protection":	IP67
Operation temp:	-30 °C ... 60 °C
Weight:	0.32 kg
Dimensions:	Ø 110 x 81 mm
Manufacturer / Brand:	DAHUA
Guarantee:	<b>3 years</b>

## PRESENTATION

Camera view after remove the Dome cover:



Mounting side view:



Camera image at night conditions with internal built-in IR illuminator on:



Camera image at direct strong light opposite to camera:



## PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------