

Code: DS-2CD2T46G2-2I(2.8mm)

## IP CAMERA **DS-2CD2T46G2-2I(2.8mm)** - 5 Mpx Hikvision

Net: **1 043.00 PLN** Gross: **1 043.00 PLN**

IP camera with efficient H.265 / H.264 image compression algorithm for clear and smooth video streaming at maximal resolution of 5 Mpx.

PoE powering possibility, compatible with the 802.3af standard makes the device more universal and easier to install.

Powered by Darkfighter - the camera has very good sensitivity, dedicated to poor lighting conditions.



### SPECIFICATION

|                           |   |
|---------------------------|---|
| Standard:                 | TCP/IP  |
| Sensor:                   | 1/2.7 " Progressive Scan CMOS   |
| Scanning system:          | Progressive   |
| Matrix size:              | 5 Mpx   |
| Resolution:               | 2592 x 1944 - 5 Mpx ,<br>2688 x 1520 - 4 Mpx ,<br>2304 x 1296 - 3 Mpx ,<br>1920 x 1080 - 1080p ,<br>1280 x 720 - 720p                                 |
| Lens:                     | 2.8 mm  |
| View angle:               | <ul style="list-style-type: none"><li>• 103 ° (manufacturer data)</li><li>• 95 ° (our tests result)</li></ul>   |
| Compression:              | H.265+ / H.265 / H.264+ / H.264 / MJPEG   |
| Range of IR illumination: | 60 m  |
| Alarm inputs / outputs:   | —   |
| Audio:                    | —   |
| Memory card slot:         | Micro SD memory cards up to 256GB support (possible local recording)  |
| Main stream frame rate:   | 20 fps @ 5 Mpx<br>25 fps @ 4 Mpx  |
| Network interface:        | 10/100 Base-T (RJ-45)   |
| Network protocols:        | TCP/IP, ICMP, HTTP, HTTPS, FTP, SFTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, IEEE 802.1x, QoS, IPv6, UDP, Bonjour, SSL / TLS |
| WEB Server:               | Built-in  |



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

|                                |  |
|--------------------------------|--|
| Max. number of on-line users:  | 6  |
| ONVIF:                         | ✓  |
| Mobile phones support:         | Port no.: 8000 or access by a cloud (P2P)<br><ul style="list-style-type: none"> <li>• Android: Free application <a href="#">iVMS-4500</a> or <a href="#">Hik-Connect</a></li> <li>• iOS (iPhone): Free application <a href="#">iVMS-4500</a> or <a href="#">Hik-Connect</a></li> </ul>   |
| Default admin user / password: | admin / -<br>The administrator password should be set at the first start   |
| Default IP address:            | 192.168.1.64   |
| Web browser access ports:      | 80   |
| PC client access ports:        | Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application  |
| Mobile client access ports:    | 8000   |
| Port ONVIF:                    | 80   |
| RTSP URL:                      | <ul style="list-style-type: none"> <li>• Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ - with authorization</li> <li>• Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ - with authorization</li> </ul>  |
| RS-485 interface:              | —  |
| Main features:                 | <ul style="list-style-type: none"> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners</li> <li>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Configurable Privacy Zones</li> <li>• Motion Detection</li> <li>• Sharpness - sharper image outlines</li> <li>• Camera from AcuSense series</li> <li>• Filtering of false alarms based on the recognition of persons and vehicles</li> <li>• Intelligent image analysis : intrusion, crossing the line (tripwire), detection of entry into the area / exit from the area, scene changing, face detection, advanced face capture features</li> </ul> |
| Power supply:                  | <ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 880 mA</li> </ul>   |
| Power consumption:             | <ul style="list-style-type: none"> <li>≤ 9 W @ PoE (802.3af)</li> <li>≤ 7.5 W @ 12 V DC</li> </ul>   |
| Housing:                       | Compact, Aluminum  |
| Color:                         | White  |
| "Index of Protection":         | IP67   |
| Operation temp:                | -30 °C ... 60 °C   |
| Supported languages:           | Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian   |
| Weight:                        | 1.07 kg  |
| Dimensions:                    | Ø 105 x 290 mm   |
| Manufacturer / Brand:          | Hikvision  |
| SAP Code:                      | 311311201  |
| Guarantee:                     | <b>3 years</b>   |

## PRESENTATION



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60



Side view:



Memory card slot:



Camera mounting side view:



In the kit:



## OUR TESTS

Camera image at artificial illumination (about 30Lux):



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

Camera image at night conditions with internal built-in IR illuminator on:



Camera image at direct strong light opposite to camera:



## PACKAGE

|                                  |                    |
|----------------------------------|--------------------|
| Dimensions (L x W x H): 0x0x0 mm | Gross Weight: 0 kg |
|----------------------------------|--------------------|