

Code: IPC-HFW1530S-0360B-S6

## IP CAMERA **IPC-HFW1530S-0360B-S6** 5 Mpx 3.6 mm DAHUA

Net: **324.65 AUD** Gross: **324.65 AUD**

IP camera with efficient H.265 / H.264 image compression algorithm for clear and smooth video streaming at maximal resolution of 5 Mpx.

The range of IR illumination according to the manufacturer data, depends on outer conditions (visibility - air transparency, environment, wall colors ie. scene reflectance).

PoE powering possibility, compatible with the 802.3af standard makes the device more universal and easier to install.



### SPECIFICATION

|                           |                                                                                                                                                                                                 |
|---------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Standard:                 | TCP/IP                                                                                                                                                                                          |
| Sensor:                   | 1/2.7 " Progressive Scan CMOS                                                                                                                                                                   |
| Matrix size:              | 5 Mpx                                                                                                                                                                                           |
| Resolution:               | 2880 x 1620 - 5 Mpx ,<br>2688 x 1520 - 4 Mpx ,<br>2560 x 1440 - 3.7 Mpx ,<br>2048 x 1536 - 3 Mpx ,<br>2304 x 1296 - 3 Mpx ,<br>1920 x 1080 - 1080p<br>1280 x 960 - 1.3 Mpx<br>1280 x 720 - 720p |
| Lens:                     | 3.6 mm                                                                                                                                                                                          |
| View angle:               | • 84 ° (manufacturer data)<br>• 77 (our tests result)                                                                                                                                           |
| Range of IR illumination: | 30 m                                                                                                                                                                                            |
| RS-485 interface:         | —                                                                                                                                                                                               |
| Memory card slot:         | —                                                                                                                                                                                               |
| Image compression method: | H.265+ / H.265 / H.264 / H.264+ / MJPEG                                                                                                                                                         |
| Alarm inputs / outputs:   | —                                                                                                                                                                                               |
| Audio:                    | • Microphone built-in<br>• Audio transmission via network<br>• Audio detection                                                                                                                  |
| Main stream frame rate:   | 20 fps @ 5 Mpx<br>25 fps @ 4 Mpx                                                                                                                                                                |

|                                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|--------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Network interface:             | 10/100 Base-T (RJ-45)                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Network protocols:             | IPv4/IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, SMTP, FTP, DHCP, DNS, DDNS, NTP, Multicast                                                                                                                                                                                                                                                                                                                                                                                             |
| WEB Server:                    | Built-in                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Max. number of on-line users:  | 6                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| ONVIF:                         | 20.06                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Mobile phones support:         | Port no.: 37777 or access by a cloud (P2P)<br>• Android: Free application <a href="#">DMSS</a><br>• iOS (iPhone): Free application <a href="#">DMSS</a>                                                                                                                                                                                                                                                                                                                           |
| Default IP address:            | 192.168.1.108                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Default admin user / password: | admin / -<br>The administrator password should be set at the first start                                                                                                                                                                                                                                                                                                                                                                                                          |
| Web browser access ports:      | 80, 37777                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| PC client access ports:        | 37777                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Mobile client access ports:    | 37777                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Port ONVIF:                    | 80                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| RTSP URL:                      | rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream<br>rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream                                                                                                                                                                                                                                                                                                   |
| Main features:                 | <ul style="list-style-type: none"> <li>• D-WDR - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Motion Detection</li> <li>• Privacy zones</li> <li>• Configurable Privacy Zones</li> <li>• Audio detection</li> <li>• Mirror - Mirror image</li> </ul> |
| Power supply:                  | <ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 330 mA</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                    |
| Power consumption:             | <ul style="list-style-type: none"> <li>• ≤ 3.9 W @ 12 V DC</li> <li>• ≤ 4.5 W @ PoE (802.3af)</li> </ul>                                                                                                                                                                                                                                                                                                                                                                          |
| Housing:                       | Compact - Metal                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Color:                         | White                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| "Index of Protection":         | IP67                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Operation temp:                | -40 °C ... 60 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Weight:                        | 0.47 kg                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Dimensions:                    | Ø 70 x 162 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Supported languages:           | English, Spanish, Russian                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Manufacturer / Brand:          | DAHUA                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Guarantee:                     | <b>3 years</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |

## PRESENTATION



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60




Side view:



Camera mounting side view:



Camera dimensions:




See how to initialize DAHUA cameras:

:

In the kit:



Example captures of device interface:



## OUR TESTS

Camera image at artificial illumination (about 30Lux):



Camera image at night conditions with internal built-in IR illuminator on:



Camera image at direct strong light opposite to camera:



## PACKAGE

|                                  |                    |
|----------------------------------|--------------------|
| Dimensions (L x W x H): 0x0x0 mm | Gross Weight: 0 kg |
|----------------------------------|--------------------|