

Code: CD-2-DG

CURTAIN PIR DETECTOR **CD-2-DG** SATEL

Net: **21.11 EUR** Gross: **21.11 EUR**



The curtain detector provides a narrow detection angle.

SPECIFICATION

Application:	Indoor
Pyroelectric sensor:	Double
Sensor type:	Passive Infra Red (PIR)
Range:	5 x 1 m, 15 °
Sensitivity adjustment:	✓
Alarm outputs:	NC
Prealarm feature:	—
Alarm time:	2 s
Maximal outputs load:	40 mA / 24 V DC
Digital temperature compensation:	✓
Pet immunity:	—
Power supply:	12 V DC / 7 mA (max)
Operation temp:	-10 °C ... 55 °C
Target speed range:	0.3 ... 1 m/s


Main features:	• Curtain lens • digital detection algorithm with temperature compensation for high immunity to false alarms and repeatability of parameters • Monitoring of motion detection system • Supply voltage control • Tamper detection - opening the enclosure, removing from mounting surface • LED indication • Compliance with EN 50130-4, EN 50130-5 standards • Environmental class EN 50130-5 : II
Color:	Dark graphite
Weight:	0.02 kg
Dimensions:	105 x 25 x 20 mm
Manufacturer / Brand:	SATEL
Guarantee:	2 years

PRESENTATION



Internal view:



Description of particular elements of the device:



1. cable terminals
 - +12V Power supply
 - COM - Ground
 - TMP - TAMPER output
 - NC - Alarm output
 2. LED indication
 3. potentiometer for detection sensitivity adjustment
 4. tamper contact
- Detector range:



Mounting side view:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

