

	PIR DETECTOR FPKX10DP PYRONIX	PIR DETECTOR FPKX15DQ PYRONIX	PIR DETECTOR DS-PDP18- EG2(P) Hikvision
			
	137.61 DKK 137.61 DKK	153.90 DKK 153.90 DKK	108.64 DKK 108.64 DKK
Application	Indoor	Indoor	Indoor
Pyroelectric sensor	Double	quadruple	Double
Sensor type	Passive Infra Red (PIR)	Passive Infra Red (PIR)	Passive Infra Red (PIR)
Range	10 m / 85 °	15 m / 85 °	18 m / 85.9 °
Sensitivity adjustment	Automatic	Automatic / manual - 2 - step	• Automatic • 2 - step, manual
Pet immunity	≤ 24 kg	—	10 kg - (within the zone up to 10m), requires an adapter
Maximal outputs load	50 mA / 60 V DC, 42 V AC RMS	50 mA / 60 V DC, 42 V AC RMS	...
Digital temperature compensation	✓	✓	✓
Alarm output	NC / EOL-NC / 2EOL-NC	NC / EOL-NC / 2EOL-NC	NC / EOL-NC / 2EOL-NC
Power supply	9 ... 16 V DC / 16 mA at 12 V (max)	9 ... 16 V DC / 16 mA (max) @ 12 V	9 ... 16 V DC / 11 mA @ 12 V (max)
Target speed range	0.3 ... 3 m/s	0.3 ... 3 m/s	0.3 ... 2.0 m/s
Protection class (Grade)	Grade 2	Grade 2	Grade 2
Manufacturer's code	KX10DP	KX15DQ	...

Main features	...	...	• EN 50131-2-2:2017, EN50131-1:2006+A1:2009, EN50131-1:2006+A2:2017 • Full digital control based on microprocessor technology • SEC (Smart Environmental Control) - advanced digital signal processing and 3D optics • digital detection algorithm with temperature compensation for high immunity to false alarms and repeatability of parameters • Immunity to environmental changes • Independent Floating Threshold (IFT) technology • Tamper detection - opening the enclosure • Assembly : 1.8 m ... 2.4 m • LED indication : Blue - Alarm signaling
Operation temp	-30 °C ... 70 °C	-30 °C ... 70 °C	-10 °C ... 55 °C
Weight	0.1 kg	0.1 kg	0.07 kg
Dimensions	68 x 116 x 51 mm	68 x 116 x 51 mm	87 x 65 x 46 mm
Manufacturer / Brand	PYRONIX	PYRONIX	Hikvision
SAP Code	361300082	361300084	314300065
Guarantee	5 years	5 years	2 years