

Code: 48V/3A/5.5

## SWITCHING ADAPTER 48V/3A/5.5

Net: 9 127.62 HUF Gross: 9 127.62 HUF

Switching adapter, it is designed to powering IP devices using PoE technology.  
Attention! If the power adaptor is using for continuous work (24H) the rated current of the adaptor should be less than 80% of the maximal current.  
Please pay attention for proper cooling conditions of the power adaptor during work!



### SPECIFICATION

Model identifier:	48V/3A/5.5
Input voltage:	220 - 240 V AC
AC input frequency:	50 / 60 Hz
Output voltage:	48.0 V DC
Output current:	3.0 A
Output power:	144.0 W
Average efficiency during work:	88.0 %
Efficiency at low load (10%):	80.1 %
No-load power consumption:	< 0.21 W
Connector:	2.1/5.5 mm plug on the cable
Protections:	Overload
LED indicators:	—
Housing:	Desktop - Plastic
Operation temp. / Relative humidity:	0 ... 55 °C / 10 ... 90 %
Weight:	0.34 kg
Dimensions:	136 x 58 x 40 mm
Guarantee:	2 years

### PRESENTATION



Connectors:

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60



## PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------