

Code: HAC-PT1500A-IL-A-0280B-S2

AHD, HD-CVI, HD-TVI, PAL PTZ CAMERA INDOOR **HAC-PT1500A-IL-A-0280B-S2** Smart Dual Light - 5 Mpx 2.8 mm DAHUA

Net: **133.42 EUR** Gross: **133.42 EUR**

Megapixel camera with 1/2.8" CMOS sensor and AHD / HD-CVI / HD-TVI.

The AHD / HD-CVI / HD-TVI interface allows to transmission of analog video signal via coaxial cable in max. 8 Mpx (4K UHD) resolution. During transmission there are no delays and is maintained the original, high quality image.

The device is equipped with Smart Dual Light technology, thanks to which the user has a choice of white light mode and IR (infrared) mode. When Smart Dual Light is active, the white light will turn on automatically only when an object is detected in the monitored area, which effectively improves the image quality. Thanks to the "Starlight" technology used, the camera only needs very low lighting to obtain a clear color image.

Camera is according to IP66 Index of Protection norm.



SPECIFICATION

Standard:	AHD, HD-CVI, HD-TVI, PAL
Resolution:	<ul style="list-style-type: none">• 2880 x 1620 - 5 Mpx @ HD-CVI - 25 fps : Aspect Ratio 16 : 9,• 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI - 25 fps• 1920 x 1080 - 1080p @ HD-CVI - 25 fps• 960 x 576 - 960H @ PAL
Sensor:	Progressive Scan CMOS
Range of IR illumination:	40 m
White light LED illuminator range:	40 m
Lens:	2.8 mm
View angle:	112 °
Digital zoom:	—
Horizontal rotation range:	0 ° ... 355 ° - Rotation of the head is limited by stops
Vertical rotation range:	0 ° ... 90 °
PTZ control:	The ability to control via coaxial cable from recorder
S/N ratio:	> 65 dB
Video output:	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp 75 Ω
Audio:	Microphone built-in - HD-CVI only
Number of presets:	—

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Route settings:	—
Horizontal scan:	—
Alarm inputs / outputs:	—
Main features:	<ul style="list-style-type: none"> • When Smart Dual Light is active, the white light will turn on automatically only when an object is detected in the monitored area, which effectively improves the image quality • D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • ICR - Movable InfraRed filter • BLC/HLC - Back Light / High Light Compensation • Auto White Balance • Mirror - Mirror image • Configurable Privacy Zones
OSD menu:	✓
Power supply:	12 V DC / 530 mA
Power consumption:	≤ 6.4 W (max)
Housing:	Mini Speed Dome Plastic
Color:	White + Black
"Index of Protection":	IP66
Vandal-proof:	—
Operation temp:	-40 °C ... 60 °C
Weight:	0.38 kg (with bracket)
Dimensions:	93 x 91 x 131 mm (without bracket)
Supported languages:	English
Manufacturer / Brand:	DAHUA
Guarantee:	5 years

PRESENTATION

Side view:



Bottom view:



Mounting side view:



Camera and bracket dimensions:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

