

Code: IPC-HFW1320S-W-0280B

IP CAMERA **IPC-HFW1320S-W-0280B** Wi-Fi, 3.0 Mpx 2.8 mm DAHUA

Net: **441.00 PLN** Gross: **441.00 PLN**

IP camera with efficient H.264 image compression algorithm for clear and smooth video streaming at maximal resolution of 3 MPx. The used Wi-Fi module allows to remote communication with camera for max. distance up to 50 m. The range of IR illumination according to the manufacturer data, depends on outer conditions (visibility - air transparency, environment, wall colors ie. scene reflectance).



SPECIFICATION

| | |
|---------------------------|--|
| Standard: | TCP/IP |
| Sensor: | 1/3 " Progressive Scan CMOS |
| Matrix size: | 3.0 Mpx |
| Scanning system: | Progressive |
| Resolution: | 2304 x 1296 - 3.0 Mpx |
| Lens: | 2.8 mm |
| View angle: | 100 ° |
| Range of IR illumination: | 30 m |
| S/N ratio: | > 50 dB |
| RS-485 interface: | — |
| Image compression method: | H.264 |
| Alarm inputs / outputs: | — |
| Audio: | — |
| Bitrate: | 448 kbps ... 10240 kbps - H.264 |
| Main stream frame rate: | 20 fps @ 3.0 Mpx |
| Network interface: | 10/100 Base-T (RJ-45), Wi-Fi IEEE 802.11 b/g/n |
| Network protocols: | TCP DHCP |
| WEB Server: | Built-in, NVR compliance |

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

| | |
|--------------------------------|---|
| Max. number of on-line users: | 20 |
| ONVIF: | ✓ |
| Memory card slot: | Micro SD memory cards up to 128GB support (possible local recording) |
| Main features: | <ul style="list-style-type: none"> • Wi-Fi Module - IEEE 802.11 b/g/n, Range : 50 m (open area) ; Antenna - SMA socket • Motion Detection |
| Power supply: | 12 V DC / 360 mA |
| Power consumption: | ≤ 4.4 W |
| Mobile phones support: | Access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application DMSS • iOS (iPhone): Free application DMSS |
| Default IP address: | DHCP |
| Default admin user / password: | admin / - The administrator password should be set at the first start |
| Web browser access ports: | 80, 37777 |
| PC client access ports: | 37777 |
| Mobile client access ports: | 37777 |
| Port ONVIF: | 80 |
| RTSP URL: | rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream |
| Housing: | Compact - Metal |
| Color: | White |
| "Index of Protection": | IP67 |
| Operation temp: | -10 °C ... 50 °C |
| Weight: | 0.428 kg |
| Dimensions: | 165 x 70 x 70 mm |
| Supported languages: | English |
| Manufacturer / Brand: | DAHUA |
| Guarantee: | 3 years |

PRESENTATION



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
 POL; 60-713 Poznań; Graniczna 10
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Side view:



Bottom view:



Camera mounting side view:



See how to initialize DAHUA cameras:

:
In the kit:





PACKAGE

| | |
|----------------------------------|--------------------|
| Dimensions (L x W x H): 0x0x0 mm | Gross Weight: 0 kg |
|----------------------------------|--------------------|