

Code: BCS-L-TIP14FSR3-W

IP CAMERA **BCS-L-TIP14FSR3-W** Wi-Fi - 3.7 Mpx 2.8 mm BCS Line

Net: **158.93 EUR** Gross: **158.93 EUR**

IP camera with efficient H.265 / H.264 image compression algorithm for clear and smooth video streaming at maximal resolution of 4 MPx.

The Wi-Fi module used in the device allows the device to operate also in places with limited wiring possibilities.

The range of IR illumination according to the manufacturer data, depends on outer conditions (visibility - air transparency, environment, wall colors ie. scene reflectance).



SPECIFICATION

Standard:	TCP/IP
Sensor:	1/3 " Progressive Scan CMOS
Matrix size:	3.7 Mpx
Resolution:	2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p
Lens:	2.8 mm, F2.0
View angle:	• 90 ° (manufacturer data) • 89 ° (our tests result)
Range of IR illumination:	30 m
Image compression method:	H.265+ / H.265 / H.264+ / H.264
Alarm inputs / outputs:	—
Audio:	• Microphone built-in • Noise reduction • Audio detection
Main stream frame rate:	• 20 fps @ 3.7 Mpx • 25 fps @ 3 Mpx
Network interface:	10/100 Base-T (RJ-45), 2.4 GHz Wi-Fi IEEE 802.11 b/g/n
Network protocols:	IPv4, HTTP, TCP, UDP, ARP, RTP, RTSP, RTCP, DHCP, DNS, NTP, Multicast, RTMP

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

WEB Server:	Built-in, NVR compliance, 20 on-line users
ONVIF:	21.06
Memory card slot:	Micro SD memory cards up to 256GB support (possible local recording)
Mobile phones support:	Access by a cloud (P2P) • Android: Free application BCS Manager • iOS (iPhone): Free application BCS Manager
Default admin user / password:	admin / - The administrator password should be set at the first start
Default IP address:	DHCP
Web browser access ports:	80, 37777
PC client access ports:	37777
Mobile client access ports:	37777
Port ONVIF:	80
RTSP URL:	rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
Main features:	• Wi-Fi module - 2.4 GHz IEEE 802.11 b/g/n ; Antenna - SMA socket • D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • BLC/HLC - Back Light / High Light Compensation • D-ZOOM - Digital Zoom 16 x • Mirror - Mirror image • Day/night mode • ICR - Movable InfraRed filter • Auto White Balance • AGC - Automatic Gain Control • Configurable Privacy Zones • Motion Detection • Human detection
Housing:	Compact - Metal
Color:	White
"Index of Protection":	IP67
Power supply:	12 V DC / 350 mA
Power consumption:	max. 4.1 W
Operation temp:	-40 °C ... 60 °C
Weight:	0.48 kg
Dimensions:	Ø 70 x 166 mm
Supported languages:	Polish, English
Manufacturer / Brand:	BCS Line
Guarantee:	3 years

PRESENTATION

Front view:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Side view:



Memory card slot and "Reset" button:



Antenna connector:



Camera mounting side view:



In the kit:



OUR TESTS

Camera image at artificial illumination (about 30Lux):



Camera image at night conditions with internal built-in IR illuminator on:



Camera image at direct strong light opposite to camera:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60