

Code: H2C

IP PTZ CAMERA INDOOR **H2C** Hero C1 Wi-Fi - 1080p 2.8 mm DAHUA

Net: **130.00 PLN** Gross: **130.00 PLN**



IP PTZ camera with efficient H.265 / H.264 image compression algorithm for clear and smooth video streaming at max. resolution of 1080p.

Very easy operation via mobile devices (Android / iOS), allows the users for comfortable and remote operation, and also management of the camera. The used Wi-Fi module allows to remote communication with camera for max. distance up to 50 m. The camera has no built-in web interface, configuration only through the DMSS application.

The device is ideal for eg. as a baby monitor, with mobile image view on smartphone and possibility of bi-directional audio transmission.

SPECIFICATION

Standard:	IP
Resolution:	1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p
Sensor:	1/2.8 " Progressive Scan CMOS
Lens:	2.8 mm @ F2.0
View angle:	86 °
Range of IR illumination:	15 m
Horizontal rotation range:	325 °
Vertical rotation range:	-20 ° ... 100 °
Memory card slot:	Micro SD memory cards up to 512GB support (possible local recording)
Image compression method:	Smart H.265+ / H.265 / Smart H.264+ / H.264 / H.264B / MJPEG
Alarm inputs / outputs:	—
Audio:	<ul style="list-style-type: none">• Microphone built-in,• Speakers built-in,• Bi-directional audio streaming support
Main stream frame rate:	25 fps @ 1080p
Interface:	<ul style="list-style-type: none">• 10/100 Base-T (RJ-45),• 2.4 GHz Wi-Fi IEEE 802.11 b/g/n
WEB Server:	—

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

ONVIF:	✓
Intelligent image analysis:	Intelligent recognition of the human figure and tracking the movement of a person
Main features:	<ul style="list-style-type: none"> • Wi-Fi Module - IEEE 802.11 b/g/n • Day/Night mode (color/b&w) • ICR - Movable InfraRed filter • D-WDR - Wide Dynamic Range • Image rotation and mirror • Motion Detection • Privacy Mode
Mobile phones support:	Access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application DMSS • iOS (iPhone): Free application DMSS
Default IP address:	DHCP
Default admin user / password:	admin / - The administrator password should be set at the first start
Web browser access ports:	80, 37777
PC client access ports:	37777
Mobile client access ports:	37777
Port ONVIF:	80
RTSP URL:	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
Power supply:	5 V DC / 1 A - from USB-C port (power adapter included)
Power consumption:	≤ 5 W
Housing:	Plastic
Color:	White
"Index of Protection":	—
Mechanical protection class:	—
Operation temp:	-10 °C ... 40 °C
Weight:	0.24 kg
Dimensions:	76 x 96 x 130 mm
Supported languages:	Polish, English
Manufacturer / Brand:	DAHUA
Guarantee:	3 years

PRESENTATION



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
 POL; 60-713 Poznań; Graniczna 10
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Memory card slot and "Reset" button:





Rear view:



Connectors:



Bottom view:



In the kit:



OUR OPINIONS



- Very small camera dimensions.

PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60