

Code: ETI-D3/40A

FUSE LINK **ETI-D3/40A** 40 A 500 V gG E33 ETI

Net: 6.35 PLN Gross: 6.35 PLN

Fuse-links are used as the most reliable protection of electrical installation against overload and short-circuit currents. All fuse-links have blown-fuse indicators which are visible through the screw cap when mounted.




SPECIFICATION

Rated current:	40 A
Rated voltage:	250 V DC, 500 V AC
Fusing characteristics:	gG
Fuse base:	E33
Type:	D
Size:	D3
Breaking capacity:	50 kA AC, 8 kA DC
Main features:	• Low power and energy losses • Small temperature increase • High ability to limit short-circuit current • Stability of current-time characteristics and full selectivity of operation • Selective cooperation with over-current circuit breakers
Housing:	Ceramic
Weight:	0.048 kg
Dimensions:	Ø 27 x 50 mm
Manufacturer / Brand:	ETI
Guarantee:	2 years

PRESENTATION




Dimensions:



[A]	ØA	ØB
32	27	16
35	27	16
40	27	16
50	27	18
63	27	20

Time-current characteristics:



1. Prearcing time (s)
2. Prospective current (A)

PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------