

Code: H4C

## IP PTZ CAMERA INDOOR **H4C** WizSense - 3.7 Mpx DAHUA

Net: 145.00 PLN Gross: 145.00 PLN

IP camera equipped with very good high resolution sensor. Due to above it is perfect solution for surveillance systems requiring persons or vehicles recognition.

Built-in Infra-Red illuminator enables night monitoring. The range of IR illumination according to the manufacturer data, depends on outer conditions (visibility - air transparency, environment, wall colors ie. scene reflectance).

PoE powering possibility, compatible with the 802.3at standard makes the device more universal and easier to install. Thanks to the "Starlight" technology used, the camera only needs very low lighting to obtain a clear color image.



### SPECIFICATION

Standard:	TCP/IP
Sensor:	1/2.8 " STARVIS™ CMOS
Matrix size:	4 Mpx
Resolution:	2560 x 1440 - 3.7 Mpx , 1920 x 1080 1080p , 1280 x 960 1.3 Mpx , 1280 x 720 - 720p
View angle:	80 °
Optical zoom:	—
Digital zoom:	16x
Range of IR illumination:	100 m
White light LED illuminator range:	—
Video output:	—
Horizontal rotation range:	0 ° ... 325 ° - Rotation of the head is limited by stops
Vertical rotation range:	-20 ° ... 100 °
RS-485 interface:	—
Horizontal scan:	—
Route settings:	—
Image compression method:	H.265+ / H.265 / H.264+ / H.264 / MJPEG

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Alarm inputs / outputs:	—
Main stream frame rate:	25 fps - 4 Mpx
Memory card slot:	Micro SD memory cards up to 512GB support (possible local recording)
Network interface:	10/100 Base-T (RJ-45)
WEB Server:	Built-in, NVR compliance
ONVIF:	—
Audio:	<ul style="list-style-type: none"> <li>• Microphone built-in,</li> <li>• Speaker built-in</li> <li>• Audio detection</li> <li>• Bi-directional audio streaming support</li> <li>• Audio transmission via network</li> </ul>
Mobile phones support:	Port 37777 <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">DMSS</a></li> <li>• iOS (iPhone): Free application <a href="#">DMSS</a></li> </ul>
Default admin user / password:	admin / - The administrator password should be set at the first start
Default IP address:	192.168.1.108
Web browser access ports:	80, 37777
PC client access ports:	37777
Mobile client access ports:	37777
RTSP URL:	rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
Intelligent image analysis:	People detection, Intelligent Object Tracking
Main features:	<ul style="list-style-type: none"> <li>• D-WDR - Wide Dynamic Range</li> <li>• Day/night mode</li> <li>• ICR - Movable InfraRed filter</li> <li>• Motion Detection</li> <li>• Configurable Privacy Zones</li> </ul>
Power supply:	<ul style="list-style-type: none"> <li>• PoE (802.3at) ,</li> <li>5 V DC / 1 A - from USB-C port</li> </ul>
Power consumption:	≤ 10 W
Housing:	Speed Dome, Plastic
Color:	White
"Index of Protection":	—
Mechanical protection class:	—
Operation temp:	-10 °C ... 40 °C
Weight:	0.25 kg
Dimensions:	Ø 96 x 130 mm
Supported languages:	Polish, English, Czech, French, Spanish, Dutch, Indonesian (Bahasa), German, Portuguese, Russian, Romanian, Turkish, Ukrainian, Hungarian, Vietnamese, Italian
Manufacturer / Brand:	DAHUA
Guarantee:	<b>5 years</b>

## PRESENTATION



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
 POL; 60-713 Poznań; Graniczna 10  
 e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60



Memory card slot and "Reset" button:





Rear view:



Connectors:



Bottom view:



In the kit:



## PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------