

Code: APS-612

BUFFERED SWITCHING POWER SUPPLY ADAPTER **APS-612** SATEL

Net: **1 110.00 PLN** Gross: **1 110.00 PLN**

Buffered power adapter with DIN montage casing designed to systems supplied by 12V DC voltage. The APS-612 has a special connector that enables cooperation with Satel devices.



SPECIFICATION

Adapter type:	Switching
Input voltage:	230 V AC
Output voltage:	12 V DC
Max. output current (total):	6 A
Power:	72 W
Battery charging current:	1.5 A / 3 A
Protections:	• Short-circuit • Reverse polarity connection • Overload • Overvoltage
Adapter operation control:	• DC output voltage presence indication • Battery charging indication • AC input voltage presence indication • WS output - indicating AC power collapse • WB output - Low battery voltage • WP output Current overload indication
Housing type:	Plastic, DIN, TS-35 rail mounting
Weight:	0.48 kg
Dimensions:	79 x 123 x 90 mm
Manufacturer / Brand:	SATEL
Guarantee:	2 years

PRESENTATION



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Internal view, after remove the cover:



Adapter connectors (after remove the cover):



Side view:

Satec | APS-612
Wejście/Input: 230 V AC ~50 Hz 0.4 A
Wyjście/Output: 10.5-14 V DC ~3 A
Prąd ładowania/Battery charge: max 3 A
Wyprodukowano w Polsce • Made in Poland



Mounting side view:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------