

Code: APTI-H50V21-28W

AHD, HD-CVI, HD-TVI CAMERA **APTI-H50V21-28W** 2Mpx / 5Mpx 2.8 mm

Net: **31.05 EUR** Gross: **31.05 EUR**

Megapixel camera with 1/3" CMOS sensor and AHD / HD-CVI / HD-TVI.

The AHD / HD-CVI / HD-TVI interface allows to transmission of analog video signal via coaxial cable in max. 8 Mpx (4K UHD) resolution. During transmission there are no delays and is maintained the original, high quality image.

In the case of video transmission using a twisted pair cable and matching transformers (balun), be aware of the possibility of signal reflections and interfering signals.

Attention! The camera is factory set to the resolution 2 Mpx (1080p).



SPECIFICATION

Standard:	AHD, HD-CVI, HD-TVI
Sensor:	1/3 " Progressive Scan CMOS
Matrix size:	5 Mpx
Resolution:	2592 x 1944 - 5 Mpx @ AHD / HD-TVI @ 20 fps, 12.5 fps , 2560 x 1440 - 4 Mpx @ AHD / HD-TVI @ 30 fps, 25 fps, 15 fps , 2560 x 1440 - 4 Mpx @ HD-CVI @ 30 fps, 25 fps , 1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI @ 30 fps, 25 fps
Range of IR illumination:	20 m
IR illuminator power adjustment:	Automatic
Lens:	2.8 mm
View angle:	89 °
Video output:	1 Vpp 75 Ω, AHD / HD-CVI / HD-TVI - selectable by switch
OSD menu:	✓
Main features:	<ul style="list-style-type: none">• D-WDR - Wide Dynamic Range• DNR - Digital Noise Reduction• ICR - Movable InfraRed filter• AGC - Automatic Gain Control• Day/Night mode (color/b&w/auto)• White Balance - ATW/Manual• Sharpness - sharper image outlines• Coaxial audio - HD-TVI only
Housing:	Dome - Metal

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Color:	White
Vandal-proof:	—
"Index of Protection":	IP67
Power supply:	12 V DC / 250 mA
Power consumption:	≤ 3 W
Operation temp:	-20 °C ... 60 °C
Weight:	0.28 kg
Dimensions:	Ø 93 x 77 mm
Supported languages:	Polish, English, French, Spanish, Portuguese, Russian, Italian
Manufacturer / Brand:	APTI
Guarantee:	2 years

PRESENTATION


Camera is out from clamping ring (the OSD menu controller visible):



Mounting dimensions:



The appropriate signal format selection is done by tilting and holding the joystick for 5 s without entering to the OSD menu. Changing the signal to the NTSC in the camera causes loss of image in connected AHD/HD-CVI/HD-TVI recorder:



In the kit:



OUR TESTS

AHD:

Camera image at artificial illumination (about 30Lux):



Camera image at night conditions with internal built-in IR illuminator on:



Camera image at direct strong light opposite to camera:



HD-CVI:

Camera image at artificial illumination (about 30Lux):



Camera image at night conditions with internal built-in IR illuminator on:



Camera image at direct strong light opposite to camera:



HD-TVI:

Camera image at artificial illumination (about 30Lux):



Camera image at night conditions with internal built-in IR illuminator on:



Camera image at direct strong light opposite to camera:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------