

Code: BCS-B-EA15FSR4(2.0)

AHD, HD-CVI, HD-TVI, PAL CAMERA **BCS-B-EA15FSR4(2.0)** - 5 Mpx 2.8 mm

BCS BASIC

Net: **31.47 EUR** Gross: **31.47 EUR**

Megapixel camera with 1/2.7" CMOS sensor and AHD / HD-CVI / HD-TVI / CVBS.

The AHD / HD-CVI / HD-TVI interface allows to transmission of analog video signal via coaxial cable in max. 8 Mpx (4K UHD) resolution. During transmission there are no delays and is maintained the original, high quality image.

In the case of video transmission using a twisted pair cable and matching transformers (balun), be aware of the possibility of signal reflections and interfering signals.



SPECIFICATION

Standard:	AHD / HD-CVI / HD-TVI / CVBS
Resolution:	• 2880 x 1620 - 5 Mpx @ HD-CVI @ 25 fps • 2880 x 1620 - 5 Mpx @ AHD @ 20 fps • 2880 x 1620 - 5 Mpx @ HD-TVI @ 20 fps / 12.5 fps • 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI @ 30 fps / 25 fps • 1920 x 1080 - 2 Mpx @ AHD / HD-CVI / HD-TVI @ 30 fps / 25 fps • 960 x 576 - 960H @ PAL / NTSC
Sensor:	1/2.7 " Progressive Scan CMOS
Lens:	2.8 mm
View angle:	• 109 °
Range of IR illumination:	40 m
IR illuminator power adjustment:	Automatic
Video output:	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω
OSD menu:	OSD menu available via recorder
Main features:	• D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • BLC - configurable Back Light Compensation • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Auto White Balance • Mirror - Mirror image
Power supply:	12 V DC / 283 mA
Power consumption:	< 3.4 W

Housing:	Dome, Metal
Color:	White
"Index of Protection":	IP67
Mechanical protection class:	—
Operation temp:	-20 °C ... 60 °C
Weight:	0.33 kg
Dimensions:	Ø 111 x 98 mm
Manufacturer / Brand:	BCS BASIC
Guarantee:	3 years

PRESENTATION

Camera is out from clamping ring:



Dimensions:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

