

Code: BCS-DMQ1803IR3-G

AHD, HD-CVI, HD-TVI, PAL CAMERA **BCS-DMQ1803IR3-G** - 8.3 Mpx, 4K UHD 3.6 mm

Net: 1 970.06 CZK Gross: 1 970.06 CZK

Megapixel camera with 1/2.5" Sony CMOS sensor and AHD / HD-CVI / HD-TVI / PAL.

The AHD / HD-CVI / HD-TVI interface allows to transmission of analog video signal via coaxial cable in max. 8 Mpx (4K UHD) resolution. During transmission there are no delays and is maintained the original, high quality image.

In the case of video transmission using a twisted pair cable and matching transformers (balun), be aware of the possibility of signal reflections and interfering signals.



SPECIFICATION

Standard:	AHD / HD-CVI / HD-TVI / CVBS
Sensor:	1/2.5 " SONY Starvis™ CMOS
Matrix size:	8.3 Mpx
Resolution:	3840 x 2160 - 8.3 Mpx, 4K UHD @ AHD / HD-CVI / HD-TVI, 15 fps , 2704 x 1950 - 5 Mpx @ AHD / HD-CVI / HD-TVI, 20 fps , 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI, 25 fps / 30 fps , 1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI, 25 fps / 30 fps , 1280 x 720 - 720p @ AHD / HD-CVI / HD-TVI, 25 fps / 30 fps
Range of IR illumination:	30 m
IR illuminator power adjustment:	Automatic
Lens:	3.6 mm
View angle:	100 °
Video output:	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω
Audio:	—
OSD menu:	✓
Main features:	• WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • Day/night mode • ICR - Movable InfraRed filter • Auto White Balance • AGC - Automatic Gain Control • AES - Auto Electronic Shutter • Motion Detection - max. 4 zones • Privacy zones - max. 16

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60


Power supply:	12 V DC / 420 mA
Power consumption:	< 5 W
Housing:	Dome, Metal
Color:	Dark graphite
"Index of Protection":	IP66
Vandal-proof:	—
Operation temp:	-30 °C ... 60 °C
Weight:	0.29 kg
Dimensions:	106 x 93 x 82 mm
Supported languages:	Polish, English
Manufacturer / Brand:	BCS UNIVERSAL
Guarantee:	3 years

PRESENTATION

Camera is out from clamping ring:



Dimensions:



Configuration switches:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------