

Code: BCS-B-MT82800

AHD, HD-CVI, HD-TVI, PAL CAMERA **BCS-B-MT82800** - 8.3 Mpx 4K UHD 2.8 mm BCS BASIC

Net: **64.30 EUR** Gross: **64.30 EUR**

Megapixel camera with 1/2.3" CMOS sensor and AHD / HD-CVI / HD-TVI / PAL.

The AHD / HD-CVI / HD-TVI interface allows to transmission of analog video signal via coaxial cable in max. 8 Mpx (4K UHD) resolution. During transmission there are no delays and is maintained the original, high quality image.

In the case of video transmission using a twisted pair cable and matching transformers (balun), be aware of the possibility of signal reflections and interfering signals.

The 3-Axis integrated camera bracket has a regulation in all three planes, which allows to turn the camera to any direction. The range of IR illumination according to the manufacturer data, depends on outer conditions (visibility - air transparency, environment, wall colors ie. scene reflectance). Camera is according to IP66 Index of Protection norm.



SPECIFICATION

Standard:	AHD, HD-CVI, HD-TVI, PAL
Sensor:	1/2.3 " Progressive Scan CMOS
Matrix size:	8.3 Mpx
Resolution:	3840 x 2160 - 8.3 Mpx 4K UHD , 960 x 576 - 960H, PAL
Lens:	2.8 mm, F1.2
View angle:	• 104 ° (manufacturer data) • 114 ° @ AHD, HD-TVI / 104 ° @ HD-CVI (our tests result)
Range of IR illumination:	30 m
IR illuminator power adjustment:	Automatic
Video output:	AHD / HD-CVI / HD-TVI / PAL, 1 Vpp / 75 Ω, selectable by switch
OSD menu:	✓
Main features:	• D-WDR - Wide Dynamic Range • DNR - Digital Noise Reduction • BLC - Back Light Compensation • FLC - The technology eliminates the tiring eyes flickering image effect • Sharpness - sharper image outlines • AGC - Automatic Gain Control • White Balance - ATW/Manual • Day/night mode • ICR - Movable InfraRed filter • Mirror - Mirror image
Power supply:	12 V DC / 420 mA
Power consumption:	≤ 5 W

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Housing:	Compact, Metal
Color:	Graphite
"Index of Protection":	IP66
Operation temp:	-20 °C ... 60 °C
Weight:	0.33 kg
Dimensions:	Ø 64 x 165 mm
Manufacturer / Brand:	BCS BASIC
Guarantee:	3 years

PRESENTATION

Front view:



Side view:



Camera mounting side view:



In the kit:



OUR TESTS

AHD:

Camera image at artificial illumination (about 30Lux):



Camera image at night conditions with internal built-in IR illuminator on:



Camera image at direct strong light opposite to camera:



HD-CVI:

Camera image at artificial illumination (about 30Lux):



Camera image at night conditions with internal built-in IR illuminator on:



Camera image at direct strong light opposite to camera:



HD-TVI:

Camera image at artificial illumination (about 30Lux):



Camera image at night conditions with internal built-in IR illuminator on:



Camera image at direct strong light opposite to camera:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------