






	IP MOBILE CAMERA ATE- CAM-IPC880 - 1080p 2.8 mm AUTONE	IP MOBILE CAMERA ATE- CAM-IPC765 - 1080p 2.8 mm AUTONE	IP MOBILE CAMERA ATE- CAM-IPC925 - 3.7 Mpx 2.8 mm AUTONE	IP MOBILE CAMERA DS-2XM6522G0-IM/ND - 1080p 2.8 mm Hikvision	IP MOBILE CAMERA DS-2XM6522G0-IM/ND(4mm)C - 1080p 4.0 mm Hikvision
					
	248.00 PLN 248.00 PLN	254.40 PLN 254.40 PLN	248.00 PLN 248.00 PLN	1515.00 PLN 1515.00 PLN	1515.00 PLN 1515.00 PLN
Standard	TCP/IP	TCP/IP	TCP/IP	TCP/IP	TCP/IP
Sensor	1/2.8 " CMOS	1/2.8 " CMOS	1/2.7 " SC2235 CMOS	1/2.8 " Progressive Scan CMOS	1/2.8 " Progressive Scan CMOS
Scanning system	Progressive	Progressive
Matrix size	2.1 Mpx	2.1 Mpx	3.7 Mpx	2.1 Mpx	2.1 Mpx
Resolution	1920 x 1080 - 1080p	1920 x 1080 - 1080p	2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p	1920 x 1080 - 1080p 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p	1920 x 1080 - 1080p 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p
Lens	2.8 mm	2.8 mm	2.8 mm	2.8 mm	4.0 mm
View angle	93 °	93 °	• 95 ° (manufacturer data) • 87 ° (our tests result)	• 104 °	• 77 ° (manufacturer data) • 74 ° (our tests result)
Compression	H.265+ / H.265 / H.264+ / H.264 / MJPEG	H.265+ / H.265 / H.264+ / H.264 / MJPEG
S/N ratio	≥ 58 dB	≥ 50 dB	≥ 58 dB
Range of IR illumination	15 m	10 m	10 m	10 m	10 m
Memory card slot	—	—	—	—	—
Image compression method	H.265 / H.264	H.265 / H.264	H.265, H.264
Alarm inputs / outputs	—	—	—	—	—
Audio	—	—	—	—	—
Main stream frame rate	25 fps @ 3.7 Mpx	25 fps @ 1080p	25 fps @ 1080p
Network interface	10/100 Base-T - M12, 6-pin socket - Code A	10/100 Base-T - M12, 6-pin socket - Code A	10/100 Base-T - M12, 6-pin socket - Code A	10/100 Base-TX The connection cable has been terminated with the M12 connector	10/100 Base-TX, M12, 4-pin socket - code D
Default user password	admin / -	admin / -	Information on the camera and packaging label
Network protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, IEE802.1x, QoS, IPv6, Bonjour	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, IEE802.1x, QoS, IPv6, Bonjour
WEB Server	Built-in	Built-in
Max. number of on-line users	20	20
ONVIF	✓	✓	✓	✓	✓
Mobile phones support	—	—	—	Port no.: 8000 or access by a cloud (P2P) • Android: Free application iVMS-4500 or Hik-Connect • iOS (iPhone): Free application iVMS-4500 or Hik-Connect	Port no.: 8000 or access by a cloud (P2P) • Android: Free application Hik-Connect • iOS: Free application Hik-Connect
Default admin user / password	admin / -	admin / - The administrator password should be set at the first start
Default IP address	Information on the camera and packaging label	Information on the camera and packaging label	Information on the camera and packaging label	192.168.1.64	192.168.1.64
Web browser access ports	8899	8899	8899	80	80
PC client access ports	8899	8899	8899	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application
Mobile client access ports	8000	8000
Port ONVIF	80	80
RTSP URL	• Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101 - with authorization • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102 - with authorization	• Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/
RS-485 interface	—	—	—	—	—
Main features	<ul style="list-style-type: none"> • Motion Detection • Auto White Balance • AGC - Automatic Gain Control • BLC - Back Light Compensation 	<ul style="list-style-type: none"> • Auto White Balance • AGC - Automatic Gain Control • BLC - Back Light Compensation • WDR - Wide Dynamic Range 	<ul style="list-style-type: none"> • Motion Detection • Auto White Balance • AGC - Automatic Gain Control • BLC - Back Light Compensation 	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • EIS - Electronic Image Stabilization • ROI - improve the quality of selected parts of image • F-DNR (Defog) - Reduction of image noise caused by precipitation • EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners • HLC - High Light Compensation (spot) • BLC - Back Light Compensation • Possibility to change the resolution, quality and bit rate • Mirror - Mirror image • Configurable Privacy Zones • Lens focus loss detection • The device has a built-in heater • Intelligent image analysis : Motion Detection, intrusion, crossing the line (tripwire), detection of entry into the area / exit from the area, abandoned/missing object, scene changing, face detection 	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • EIS - Electronic Image Stabilization • ROI - improve the quality of selected parts of image • F-DNR (Defog) - Reduction of image noise caused by precipitation • EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners • HLC - High Light Compensation (spot) • BLC - Back Light Compensation • Possibility to change the resolution, quality and bit rate • Mirror - Mirror image • Configurable Privacy Zones • Lens focus loss detection • The device has a built-in heater • Intelligent image analysis : Motion Detection, intrusion, crossing the line (tripwire), detection of entry into the area / exit from the area, abandoned/missing object, scene changing, face detection
Power supply	12 V DC	12 V DC	12 V DC / 600 mA	PoE (802.3af)	PoE (802.3af)
Power consumption	≤ 5 W	≤ 8.8 W	≤ 8.8 W
Housing	Mini, Metal	Dome, Metal	Dome, Metal	Compact, Aluminum	Compact, Aluminum
Color	Black	Black	White	Black	Black
Vandal-proof	IK10	IK10
"Index of Protection"	IP67	IP67	IP65	IP68	IP68
Operation temp	-30 °C ... 70 °C	-30 °C ... 70 °C	-20 °C ... 60 °C	-40 °C ... 70 °C	-40 °C ... 70 °C

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Supported languages	Polish, English, Bulgarian, Finnish, French, Greek, Hebrew, Spanish, German, Portuguese, Russian, Romanian, Turkish, Hungarian, Italian	Polish, English, Bulgarian, Finnish, French, Greek, Hebrew, Spanish, German, Portuguese, Russian, Romanian, Turkish, Hungarian, Italian	English	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Vietnamese, Italian	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Vietnamese, Italian
Weight	0.32 kg	0.24 kg	0.29 kg	0.88 kg	0.88 kg
Dimensions	86 x 68 x 68 mm	97 x 84 x 70 mm	99 x 97 x 57 mm	164 x 123 x 65 mm	164 x 123 x 65 mm
Manufacturer / Brand	AUTONE	AUTONE	AUTONE	Hikvision	Hikvision
SAP Code	.	.	.	311311921	316400111
Guarantee	2 years	2 years	2 years	3 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00