

Code: VTO1220A

VIDEO DOORPHONE **VTO1220A** DAHUA

Net: **1 960.00 PLN** Gross: **1 960.00 PLN**



Video Doorphone is mounted in a flush-mounted housing.

ATTENTION! The device does not support the Dahua analogue system.

SPECIFICATION

Sensor:	1/3 ", 1.3 Mpx CMOS
Lens:	3.6 mm
View angle:	95 °
Display:	3.5 " TFT LCD, 320 x 240 px
proximity reader built-in:	13.56 MHz S50
Image compression method:	H.264
LED illuminator:	—
IR illuminator:	✓
Compatibility:	DAHUA
RS-485:	✓
UTP category:	UTP cat. 5e
Mobile phones support:	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS
Main features:	• Keyboard built-in, • LCD display, • Bidirectional communication, • Microphone built-in, • Speakers built-in, • Tamper detection - removing from mounting surface ,
Operation temp:	-40 °C ... 60 °C

Power supply:	12 V DC / 0.83 A
Power consumption:	≤ 10 W
Housing:	Aluminum
Color:	Silver
"Index of Protection":	IP54
Weight:	1.502 kg
Dimensions:	376 x 151 x 57 mm
Supported languages:	Polish, English, Bulgarian, Czech, Finnish, Slovenian, Slovak, Hungarian
Manufacturer / Brand:	DAHUA
Guarantee:	3 years

PRESENTATION

Front view:




Rear view:






Connectors description:



Examples of connection diagrams:



- 1. INDOOR PANEL
 - 2. VIDEO DOORPHONE
 - 3. DHI-VTNS1060A
 - 4. Switch
 - 5. System management center
 - 6. Remote client
- In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

