

	SWITCH DS-KAD7060EY FOR HIKVISION 2-WIRE VIDEO DOORPHONE SYSTEMS	SWITCH DS-KAD7061EY FOR HIKVISION 4-WIRE VIDEO DOORPHONE SYSTEMS	SWITCH DS-KAD706Y FOR HIKVISION 2-WIRE VIDEO DOORPHONE SYSTEMS	VIDEO DOORPHONE DS-KD7003EY-CME2/ALUMINUM Hikvision	VIDEO DOORPHONE DS-KD8003EY-IME2 Hikvision	INDOOR PANEL DS-KH320-WTE2 Hikvision	INDOOR PANEL DS-KH330-WTE2 Hikvision	INDOOR PANEL DS-KH330-WTE4/WHITE Hikvision	INDOOR PANEL DS-KH3300EY-WTE2 Hikvision	INDOOR PANEL DS-KH7300EY-WTE4/WHITE Hikvision	VIDEO DOORPHONE KIT DS-KIS702Y Hikvision
											
	600 00 PLN 600 00 PLN	200 00 PLN 200 00 PLN	600 00 PLN 600 00 PLN	997 00 PLN 997 00 PLN	785 00 PLN 785 00 PLN	794 00 PLN 799 00 PLN	1060 00 PLN 1060 00 PLN	1060 00 PLN 1060 00 PLN	2077 00 PLN 2077 00 PLN	1060 00 PLN 1060 00 PLN	2290 00 PLN 2290 00 PLN
Doorbell button	...	...	...	2 pcs	1 pcs	...	...	...	...	...	1 pcs
Sensor	...	...	...	2 Mpx	2.1 Mpx CMOS	...	...	...	...	...	2.1 Mpx CMOS
Camera resolution	...	...	...	133°	146°	...	...	...	...	...	133° x 1080 - 1080p
Camera view angle	...	...	...	H.264	H.264	...	...	...	...	...	146°
Image compression method	...	...	...	✓	✓	...	...	...	...	...	✓
IR illuminator	...	...	...	1 x NO/NC	2 x NO/NC	...	...	...	...	...	TC/PHP, RTSP, SIP
Network protocols	...	...	...	IP65	IP65	...	...	...	...	...	2 x NO/NC
Relay outputs	...	...	...	IK10	...	...	...	...	...	...	IP65
"Index of Protection"	...	...	...	...	...	7" - capacitive touch screen	7" - capacitive touch screen	7" - capacitive touch screen	7" - capacitive touch screen	7" - capacitive touch screen	7" - capacitive touch screen
Mechanical protection class	...	...	...	...	...	1024 x 600	1024 x 600	1024 x 600	1024 x 600	1024 x 600	1024 x 600
Shield	...	...	...	...	...	128 MB (built-in)	128 MB (built-in)	128 MB (built-in)	128 MB (built-in)	128 MB (built-in)	128 MB (built-in)
Resolution	...	...	...	...	...	Wi-Fi Module - IEEE 802.11 b/g/n, • Microphone built-in, • Speakers built-in, • Bidirectional communication, • Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume. • Automatically capture and save photos if there is no response to the bell button, • IP Hikvision cameras support.	Wi-Fi Module - IEEE 802.11 b/g/n, • Microphone built-in, • Speakers built-in, • Bidirectional communication, • Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume. • Automatically capture and save photos if there is no response to the bell button, • IP Hikvision cameras support.	Wi-Fi Module - IEEE 802.11 b/g/n, • Microphone built-in, • Speakers built-in, • Bidirectional communication, • Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume. • Automatically capture and save photos if there is no response to the bell button, • IP Hikvision cameras support.	Wi-Fi Module - IEEE 802.11 b/g/n, • Microphone built-in, • Speakers built-in, • Bidirectional communication, • Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume. • Automatically capture and save photos if there is no response to the bell button, • IP Hikvision cameras support.	Wi-Fi Module - IEEE 802.11 b/g/n, • Microphone built-in, • Speakers built-in, • Bidirectional communication, • Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume. • Automatically capture and save photos if there is no response to the bell button, • IP Hikvision cameras support.	Wi-Fi Module - IEEE 802.11 b/g/n, • Microphone built-in, • Speakers built-in, • Bidirectional communication, • Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume. • Automatically capture and save photos if there is no response to the bell button, • IP Hikvision cameras support.
Internal memory	...	...	...	...	...	...	...	...	...	...	...
Main features	...	...	...	...	...	...	...	...	...	...	...
Controlling	...	...	...	...	...	capacitive touch screen	capacitive touch screen	capacitive touch screen	Touch control keys + capacitive touch screen	Touch control keys + capacitive touch screen	capacitive touch screen
Default administrator password	...	...	...	...	...	...	...	...	...	...	...
Default password for securing the zone	...	...	...	...	...	...	...	...	...	...	...
Alarm inputs	...	...	...	2 pcs	4 pcs	...	...	...	...	...	4 pcs
Alarm outputs	...	...	...	...	...	2	2	2	1	1	2
Power consumption	≤ 15 W - CH1 / CH2 ≤ 110 W - CH3 ... CH6 (total)	< 2 W	≤ 6 W - CH1 ... CH5 ≤ 16 W - CH6	< 6 W	< 4 W	≤ 6 W	≤ 4 W	≤ 4 W	≤ 5 W	≤ 5 W	< 4 W ≤ 4 W
Number of mounted modules	...	...	...	...	...	...	...	...	...	...	1 pcs
Material	...	...	...	...	...	...	...	...	...	...	Aluminum
Color	...	...	...	Black	Black	Black + Silver	Black + Silver	White	Black + Silver	White + Silver	Black Black + Silver Granite
External dimensions	...	...	...	...	...	...	...	...	...	...	117 x 107 x 37 mm
Number of ports	6 x HIKVISION 2-wire : • CH1, CH2 : max. 15 W each • CH3 ... CH6 : max. 110 W Total 2 x HIKVISION 2-wire - Uplink	4 x HIKVISION 2-wire ( Total max. 20 W ), 2 x HIKVISION 2-wire - Uplink	6 x HIKVISION 2-wire ( 1 x max. 16 W ), 2 x HIKVISION 2-wire - Uplink 1 x RJ-45	...	...	...	...	...	...	...	6 x HIKVISION 2-wire ( 4 x device, 2 x Possibility to connecting in cascade ), 1 x RJ-45
Compatibility	HIKVISION 2-wire - EY series	HIKVISION 2-wire - EY series	HIKVISION 2-wire - Y series	HIKVISION 2-wire - EY series	HIKVISION 2-wire - Y series	HIKVISION 2-wire modular video doorphones	HIKVISION 2-wire - Y series	HIKVISION 2-wire - Y series	HIKVISION 2-wire modular video doorphones	HIKVISION 2-wire modular video doorphones	HIKVISION 2-wire - Y series HIKVISION 2-wire - Y series HIKVISION 2-wire - Y series
Main features	...	...	...	...	...	...	...	...	...	...	...
Power supply	48 V DC	48 V DC - From the master switch DS-KAD7060EY	24 V DC	• 48 V DC - HIKVISION 2-wire, • 12 V DC	• 24 V DC - HIKVISION 2-wire	• 24 V DC - HIKVISION 2-wire - Y series	• 24 V DC - HIKVISION 2-wire - Y series	• 24 V DC - HIKVISION 2-wire - Y series	• 48 V DC - HIKVISION 2-wire	• 48 V DC - HIKVISION 2-wire	• 24 V DC - HIKVISION 2-wire • 24 V DC - HIKVISION 2-wire • 24 V DC
Housing	Plastic	Plastic	Plastic	Metal	Metal	...	...	...	...	...	Metal + Plastic Plastic
Operation temp	-10 °C ... 55 °C	-10 °C ... 55 °C	-10 °C ... 55 °C	-40 °C ... 60 °C	-40 °C ... 60 °C	-10 °C ... 50 °C	-10 °C ... 50 °C	-10 °C ... 50 °C	-10 °C ... 50 °C	-10 °C ... 50 °C	40 °C ... 60 °C -10 °C ... 50 °C -10 °C ... 55 °C
Weight	0.33 kg	0.08 kg	0.27 kg	0.28 kg	0.38 kg	0.33 kg	0.32 kg	0.32 kg	0.35 kg	0.35 kg	0.38 kg 0.32 kg 0.22 kg 0.25 kg

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel.:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Dimensions	144 x 93 x 66 mm	71 x 60 x 25 mm	144 x 90 x 66 mm	100 x 98 x 35 mm	100 x 98 x 44 mm	200 x 140 x 25 mm	200 x 140 x 25 mm	200 x 140 x 25 mm	190 x 138 x 20 mm	190 x 138 x 20 mm	100 x 98 x 44 mm 200 x 140 x 25 mm 144 x 90 x 66 mm
Supported languages	--	--		Polish, English, Bulgarian, Croatian, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Romanian, Serbian, Hungarian, Italian	Polish, English, Bulgarian, Croatian, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Romanian, Serbian, Hungarian, Italian	Polish, English, Bulgarian, Croatian, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Romanian, Serbian, Hungarian, Italian	Polish, English, Bulgarian, Croatian, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Romanian, Serbian, Hungarian, Italian	Polish, English, Bulgarian, Croatian, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Romanian, Serbian, Hungarian, Italian	Polish, English, Bulgarian, Croatian, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Romanian, Serbian, Hungarian, Italian	Polish, English, Bulgarian, Croatian, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Romanian, Serbian, Hungarian, Italian	Polish, English, Bulgarian, Croatian, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Romanian, Serbian, Hungarian, Italian
Manufacturer / Brand	Hikvision	Hikvision	Hikvision	Hikvision	Hikvision	Hikvision	Hikvision	Hikvision	Hikvision	Hikvision	Hikvision
SAP Code	305304203	305304457	305303644	305304875	305303968	305301738	305303991	305304183	305304184	305304860	305303992
Guarantee	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00