

Code: DS-KAD706Y

SWITCH **DS-KAD706Y** FOR HIKVISION 2-WIRE VIDEO DOORPHONE SYSTEMS

Net: **600.00 PLN** Gross: **600.00 PLN**

The device has 6 2-wire buses for connecting the monitors and external panels (power supply and signal transmission) and 1 Ethernet socket for connecting the LAN network. In addition, one of the ports is adapted to power an extensive gate station with a maximum power consumption of 16W. In addition, the switch is equipped with additional 2-wire bus outputs for cascading connection with DS-KAD706Y / DS-KAD706Y-S.

The switch can also be connected to the LAN network, which allows access to the gate opening and the option of receiving a call from the video doorphone via the mobile application. When connecting a cascade of devices to the LAN network, it is recommended to connect the DS-KAD706Y-S switch to it.



SPECIFICATION

Number of ports:	6 x HIKVISION 2-wire (1 x max. 16 W) , 2 x HIKVISION 2-wire - Uplink 1 x RJ-45
Compatibility:	HIKVISION 2-wire - Y series
Main features:	• Possibility to connecting in cascade • DIN, TS-35 rail mounting
Power supply:	24 V DC
Power consumption:	< 6 W - CH1 ... CH5 < 16 W - CH6
Housing:	Plastic
Operation temp:	-10 °C ... 55 °C
Weight:	0.27 kg
Dimensions:	144 x 90 x 66 mm
SAP Code:	305303644
Manufacturer / Brand:	Hikvision
Guarantee:	3 years

PRESENTATION


Front view:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Connectors view:



Mounting side view:





Connection schematic diagram:



1. Indoor Panel
2. Video doorphone
3. Router
4. Power adapter
5. 1-pair cable
6. Twisted-pair cable
7. Wi-Fi
8. Power supply cable

PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------