

Code: UT-50C

## UNIVERSAL METER UT-50C UNI-T

Net: **136.12 PLN** Gross: **136.12 PLN**



The UT-50C is a universal digital meter used to measure: voltage, current, resistance, capacitance, frequency, and checking the correctness of diodes operation.

### SPECIFICATION

DC voltage measurement:	200 mV $\pm$ (0.5% + 1) @ 0.1 mV , 2 V $\pm$ (0.5% + 1) @ 0.001 V , 20 V $\pm$ (0.5% + 1) @ 0.01 V , 200 V $\pm$ (0.5% + 1) @ 0.1 V , 1000 V $\pm$ (0.8% + 2) @ 1 V
AC voltage measurement:	2 V $\pm$ (0.8% + 3) @ 0.001 V , 20 V $\pm$ (0.8% + 3) @ 0.01 V , 200 V $\pm$ (0.8% + 3) @ 0.1 V , 750 V $\pm$ (1.2% + 3) @ 1 V
DC current measurement:	20 mA $\pm$ (0.8% + 1) @ 0.01 mA , 200 mA $\pm$ (1.5% + 1) @ 0.1 mA , 20 A $\pm$ (2% + 5) @ 0.01 A
AC current measurement:	20 mA $\pm$ (1% + 3) @ 0.01 mA , 200 mA $\pm$ (1.8% + 3) @ 0.1 mA , 20 A $\pm$ (3% + 5) @ 0.01 A
Resistance measurement:	200 $\Omega$ $\pm$ (0.8% + 3) @ 0.1 $\Omega$ , 2 k $\Omega$ $\pm$ (0.8% + 1) @ 0.001 k $\Omega$ , 20 k $\Omega$ $\pm$ (0.8% + 1) @ 0.01 k $\Omega$ , 200 k $\Omega$ $\pm$ (0.8% + 1) @ 0.1 k $\Omega$ , 2 M $\Omega$ $\pm$ (0.8% + 1) @ 0.001 M $\Omega$ , 200 M $\Omega$ $\pm$ (5%(RD-10) + 10) @ 0.1 M $\Omega$ *  *RD - reading value
Capacitance measurement:	20 nF $\pm$ (4% + 3) @ 0.01 nF , 200 nF $\pm$ (4% + 3) @ 0.1 nF , 2 $\mu$ F $\pm$ (4% + 3) @ 0.001 $\mu$ F , 100 $\mu$ F $\pm$ (5% + 4) @ 0.1 $\mu$ F
Inductance measurement:	-

Frequency measurement:	2 kHz ± (2% + 5) @ 1 Hz, 20 kHz ± (1.5% + 5) @ 10 Hz
Temperature measurement:	<ul style="list-style-type: none"> <li>• °C -40 ... 0 °C ± (3% + 3) @ 1 °C 0 ... 400 °C ± (1% + 3) @ 1 °C 400 ... 1000 °C ± (2.5%) @ 1 °C,</li> <li>• °F -40 ... 32 °F ± (3% + 4) @ 1 °F 32 ... 752 °F ± (1% + 4) @ 1 °F 752 ... 1832 °F ± (1.5% + 15) @ 1 °F</li> </ul>
Automatic change of measuring ranges:	—
hFE:	—
Diode test:	✓
Sound signal of the continuity test:	✓
Checking TTL logic states:	—
RS-232:	—
Main features:	<ul style="list-style-type: none"> <li>• Large, readable LCD display with backlight</li> <li>• Freezing the last reading</li> <li>• Low battery level alarm</li> <li>• Aesthetic and solid construction</li> <li>• The set includes short test leads with crocodile clips</li> </ul>
Power supply:	9V, type 6F22 battery - included
Weight:	0.28 kg
Dimensions:	167 x 83 x 42 mm
Manufacturer / Brand:	UNI-T
Guarantee:	2 years

## PRESENTATION

Front panel:



Rear view:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Place for 9V battery:



In the kit:



## PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60