

Code: UT-890D+

UNIVERSAL METER **UT-890D+** UNI-T

Net: **97.44 PLN** Gross: **97.44 PLN**



The UT-890D+ is a universal digital meter used to measure: voltage, current, resistance, capacity, frequency, hFE, temperature and checking the correct operation of diodes. Additionally, the UT-890D+ has an electric field detection (NCV) function.

The meter is equipped with the True RMS transducer enabling accurate measurement of the RMS current and voltage for both sinusoidal and distorted waveforms.

SPECIFICATION

DC voltage measurement:	600 mV $\pm$ (0.5% + 5) @ 0.1 mV , 6 V $\pm$ (0.5% + 2) @ 0.001 V , 60 V $\pm$ (0.5% + 2) @ 0.01 V , 600 V $\pm$ (0.5% + 2) @ 0.1 V , 1000 V $\pm$ (0.7% + 5) @ 1 V
AC voltage measurement:	6 V $\pm$ (1.0% + 3) @ 0.001 V , 60 V $\pm$ (0.8% + 3) @ 0.01 V , 600 V $\pm$ (0.8% + 3) @ 0.1 V , 750 V $\pm$ (1.0% + 10) @ 1 V
DC current measurement:	60 μ A $\pm$ (0.8% + 8) @ 0.01 μ A , 600 μ A $\pm$ (0.8% + 8) @ 0.1 μ A , 6 mA $\pm$ (0.8% + 8) @ 0.001 mA , 60 mA $\pm$ (0.8% + 8) @ 0.01 mA , 600 mA $\pm$ (1.2% + 5) @ 0.1 mA , 20 A $\pm$ (2.0% + 5) @ 0.01 A
AC current measurement:	60 μ A $\pm$ (1% + 12) @ 0.01 μ A , 600 μ A $\pm$ (1% + 12) @ 0.1 μ A , 6 mA $\pm$ (1% + 12) @ 0.001 mA , 60 mA $\pm$ (1% + 12) @ 0.01 mA , 600 mA $\pm$ (2% + 3) @ 0.1 mA , 20 A $\pm$ (3% + 5) @ 0.01 A
Resistance measurement:	600 Ω $\pm$ (0.8% + 5) @ 0.1 Ω , 6 k Ω $\pm$ (0.8% + 3) @ 0.001 k Ω , 60 k Ω $\pm$ (0.8% + 3) @ 0.01 k Ω , 600 k Ω $\pm$ (0.8% + 3) @ 0.1 k Ω , 6 M Ω $\pm$ (0.8% + 3) @ 0.001 M Ω , 60 M Ω $\pm$ (3% + 10) @ 0.01 M Ω



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Capacitance measurement:	6 nF ± (4% + 10) @ 0.001 nF , 60 nF ± (4% + 10) @ 0.01 nF , 600 nF ± (4% + 10) @ 0.1 nF , 6 µF ± (3% + 10) @ 0.001 µF , 60 µF ± (3% + 10) @ 0.01 µF , 600 µF ± (3% + 10) @ 0.1 µF , 6 mF ± (5% + 10) @ 0.001 mF , 60 mF ± 10 % @ 0.01 mF , 100 mF ± 10 % @ 0.1 mF
Inductance measurement:	—
Frequency measurement:	9.999 Hz ... 9.999 MHz ± (0.1% + 5) @ 0.001 Hz ... 0.001 MHz
Temperature measurement:	—
Automatic change of measuring ranges:	—
hFE:	✓
Diode test:	✓
Sound signal of the continuity test:	✓
Checking TTL logic states:	—
RS-232:	—
USB:	—
Main features:	• True RMS - accurate measurement of the RMS current and voltage for any waveform, • NCV - electric field detection function, • LIVE - voltage tester function, it is used to quickly determine whether a cable or socket is live using only one test probe, • Freezing the last reading, • Freezing the highest or lowest measurement, • Automatic shutdown after 15 minutes of inactivity, • Large, readable LCD display with backlight, • Low battery level alarm, • Aesthetic and solid construction
Power supply:	2 x 1.5V, type AAA/LR03 battery
Weight:	0.34 kg
Dimensions:	183 x 88 x 56 mm
Manufacturer / Brand:	UNI-T
Guarantee:	2 years

PRESENTATION

Front panel:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Rear view:



Place for batteries 2 x 1.5V AAA:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------