

Code: UT-125C

UNIVERSAL METER **UT-125C** UNI-T

Net: **24.82 EUR** Gross: **24.82 EUR**

UT-125C is a universal digital meter used to measure: voltage, resistance, diodes, continuity, frequency, duty cycle factor.



SPECIFICATION

DC voltage measurement:	400 mV \pm (1% + 8) @ 0.1 mV , 4 V \pm (0.5% + 5) @ 0.001 V , 40 V \pm (0.5% + 5) @ 0.01 V , 400 V \pm (0.5% + 5) @ 0.1 V , 600 V \pm 0.8% + 5) @ 1 V
AC voltage measurement:	4 V \pm (1.2% + 5) @ 0.001 V , 40 V \pm (1.2% + 5) @ 0.01 V , 400 V \pm (2.0% + 10) @ 0.1 V , 600 V \pm (2.0% + 10) @ 1 V
DC current measurement:	400 μ A \pm (1.8% + 5) @ 0.1 μ A , 4 μ A \pm (1.8% + 5) @ 0.001 mA , 40 mA \pm (1.8% + 5) @ 0.01 mA , 400 mA \pm (1.8% + 5) @ 0.1 mA
AC current measurement:	400 μ A \pm (2.0% + 8) @ 0.1 μ A , 4 mA \pm (2.0% + 8) @ 0.001 mA , 40 mA \pm (2.0% + 8) @ 0.01 mA , 400 mA \pm (2.0% + 8) @ 0.1 mA ,
Resistance measurement:	400 Ω \pm (1% + 5) @ 0.1 Ω , 4 k Ω \pm (1% + 5) @ 0.001 k Ω , 40 k Ω \pm (1% + 5) @ 0.01 k Ω , 400 k Ω \pm (1% + 5) @ 0.1 k Ω , 4 M Ω \pm (1.2% + 10) @ 0.001 M Ω , 40 M Ω \pm (2.0% + 10) @ 0.01 M Ω
Capacitance measurement:	50 nF \pm (4.0% + 30) @ 0.01 nF , 500 nF \pm (3% + 15) @ 0.1 nF , 5 μ F \pm (4.0% + 10) @ 1 nF , 50 μ F \pm (4.0% + 10) @ 10 nF , 100 μ F \pm (4.0% + 10) @ 100 nF
Inductance measurement:	—
Frequency measurement:	9.999 Hz ~ 60 kHz \pm (0.1% + 5) @ 0.001 Hz ~ 0.01 MHz
Square-wave signal duty ratio measurement:	—
Temperature measurement:	—

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Automatic change of measuring ranges:	✓
hFE:	—
Diode test:	✓
Sound signal of the continuity test:	✓
Checking TTL logic states:	—
RS-232:	—
Main features:	<ul style="list-style-type: none"> • Large, readable LCD display • Freezing the last reading • Low battery level alarm • Aesthetic and solid construction • Length of the cables - 75 cm
Power supply:	2 x 1.5V, type AAA/LR03 battery - included
Weight:	0.164 kg
Dimensions:	110 x 58 x 35 mm
Manufacturer / Brand:	UNI-T
Guarantee:	2 years

PRESENTATION



Front panel:



Rear view:



Place for batteries 2 x 1.5V AAA:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------