

Code: UT-501B

INSULATION RESISTANCE METER **UT-501B** UNI-T

Net: **71.88 EUR** Gross: **71.88 EUR**



The meter UT-501B is a specialized device designed to measure insulation resistance in the range from $0\text{M}\Omega$ to $5.5\text{G}\Omega$.

Attention! High voltage is required to correctly measure the insulation resistance value. During the measurement one should be particularly careful and strictly follow the recommendations included in the device manual.

SPECIFICATION

Resistance measurement:	<ul style="list-style-type: none">• Test voltage 250 V : 0 ... $5.5\text{G}\Omega$• Test voltage 500 V : 0 ... $5.5\text{G}\Omega$• Test voltage 1000 V : 0 ... $5.5\text{G}\Omega$
Measuring accuracy:	<ul style="list-style-type: none">• $0\text{M}\Omega$... $99.9\text{M}\Omega \pm (3\% + 5)$• $100\text{M}\Omega$... $5.5\text{G}\Omega \pm (5\% + 5)$
Open circuit voltage:	Test voltage + 10 %
Test current:	1 mA ... 1.1 mA
Short-circuit current:	< 2 mA
AC voltage measurement:	30 V ... $750\text{V} \pm (2\% + 3)$ @ 1 V
DC voltage measurement:	—
Measurement of small resistances:	0Ω ... $200\Omega \pm (2\% + 3)$ @ 0.01 Ω
Automatic change of measuring ranges:	✓
RS-232:	—
USB:	—
Main features:	<ul style="list-style-type: none">• Warning of using high voltage during the measurement,• Polarization index measurement (PI),• Measurement of dielectric absorption : 60s / 15s, 60s / 30s,• Automatic power-off,• Reset function for measuring low resistances,• Large, readable LCD display with backlight,• Low battery level alarm,• Aesthetic and solid construction

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Operation temp:	0 °C ... 40 °C
Permissible relative humidity:	≤ 85 % (non-condensing)
Power supply:	6 x 1.5V, type AA/LR6/FR6 battery - included
Weight:	0.42 kg
Dimensions:	150 x 100 x 71 mm
Manufacturer / Brand:	UNI-T
Guarantee:	2 years

PRESENTATION

Front panel:



Front panel cover:



Rear view:

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
 POL; 60-713 Poznań; Graniczna 10
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Place for batteries 6 x 1.5V AA:



In the kit:



Device is secured by handy case:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60