

Code: APTI-W31S2-TUYA

PTZ OUTDOOR IP CAMERA **APTI-W31S2-TUYA** Tuya Smart Wi-Fi, - 3 Mpx 3.6 mm

Net: **30.70 EUR** Gross: **30.70 EUR**

The cameras cooperating with the user-friendly Tuya platform have been designed with special care to simplify the configuration process and enable the user to create a simple and effective monitoring system.

The free Tuya Smart application will send a notification to your phone when the sensors in the camera detect movement or sound, and you can control the device at any time, regardless of where you are - all you need is Internet access and a smartphone.

Tuya Smart application works perfectly with Google Assistant, Amazon Alexa and many others, which allows you to control connected devices using voice commands. The additional Video IPC streaming service enables the display of images from cameras and ringtones, e.g. on a TV screen.

Attention! Devices cooperating with the Tuya platform do not have a WEB interface. The camera works only with the mobile application (the camera does not work with recorders). Controlling the device and schedule settings is possible if the device has access to the Internet.



SPECIFICATION

Standard:	TCP/IP
Sensor:	Progressive Scan CMOS
Resolution:	2304 x 1296 - 3 Mpx
Lens:	3.6 mm
View angle:	67 °
Range of IR illumination:	15 m
White light LED illuminator range:	15 m
Horizontal rotation range:	0 ° ... 270 ° Rotation of the head is limited by stops
Vertical rotation range:	0 ° ... 90 °
Audio:	<ul style="list-style-type: none">• Microphone built-in,• Speaker built-in,• Audio transmission via network,• Bi-directional audio streaming support
Main stream frame rate:	25 fps
Network interface:	<ul style="list-style-type: none">• Wi-Fi - IEEE 802.11 b/g/n,• Ethernet - 10 / 100 Mbps (RJ-45)
ONVIF:	—
WEB Server:	—

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Mobile phones support:	Access by a cloud (P2P) <ul style="list-style-type: none"> • The Tuya Smart free application on Android • The Tuya Smart free application on iOS
Default IP address:	DHCP
Web browser access ports:	—
PC client access ports:	—
Mobile client access ports:	—
Port ONVIF:	—
RTSP URL:	—
Memory card slot:	Micro SD memory cards up to 128GB support (possible local recording)
Main features:	<ul style="list-style-type: none"> • Wi-Fi Module - IEEE 802.11 b/g/n, Range : 30 m (open area) • Cooperation of the Tuya Smart application with Google Assistant, Amazon Alexa • RESET button
Power supply:	• 12 V DC / 1.5 A (power adapter included)
Power consumption:	≤ 6 W
Housing:	Mini Speed Dome, Plastic
Weight:	0.47 kg
Dimensions:	171 x 110 x 180 mm
Operation temp:	-10 °C ... 60 °C
Supported languages:	English
Guarantee:	2 years

PRESENTATION

Rear view:



Memory card slot and "Reset" button:



Camera mounting dimensions:




Camera connectors:



In the kit:



Sample interface screenshot:



OUR TESTS

Camera image at artificial illumination (about 30Lux):



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Camera image at night conditions with internal built-in LED illuminator on:



Camera image at night conditions with internal built-in IR illuminator on:



Camera image at direct strong light opposite to camera:



OUR OPINIONS



- Small dimensions of the camera.

PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------