

Code: RG-EG105GW(T)

ROUTER WIFI **RG-EG105GW(T)** Wi-Fi 5, 867 Mbps + 400 Mbps REYEE

Net: **618.00 PLN** Gross: **618.00 PLN**



The RG-EG105GW(T) Gigabit VPN Router supports many VPN protocols, providing high performance and high security. Operation integrated with the Ruijie Cloud platform enables central management from the cloud and Ruijie Reyee application.

4 Gigabit Ethernet WAN ports with bandwidth load balance raise the utilization rate of multi-line broadband.

SPECIFICATION

Frequency range:	2.4 GHz, 5 GHz
Antenna type:	2x2 MIMO - built-in • 3 dBi @ 2.4 GHz • 4 dBi @ 5 GHz
Standards:	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, 802.3z, IEEE 802.11 a/b/g/n/ac, Wi-Fi 5
Baud rates:	867 Mbps @ 5 GHz + 400 Mbps @ 2.4 GHz
LAN ports:	• 1 x LAN 10/100/1000 Mbps (RJ-45) • 3 x LAN/WAN 10/100/1000 Mbps (RJ-45)
WAN interface:	• 1 x WAN x 10/100/1000 Mbps (RJ-45)
LED indicators:	Status, Link/Act, Mesh
DDNS:	✓
DHCP server:	✓
Port USB:	✓
Firmware update:	✓
Power supply PoE:	—



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Protections:	• TCP scan blocking • ACL • IP-MAC Binding • MAC addresses filtering • Support for dynamic ARP mapping and static table • NAT / NAPT • Port Mapping • Mechanisms to prevent the most common types of DoS (Denial-of-Service) attacks
Management interface:	• Ruijie Cloud Central Management System • Configuration using the Ruijie Reyee application • Remote management • Web browser
Mobile phones support:	Android: Free application Ruijie Reyee iOS (iPhone): Free application Ruijie Reyee
Main features:	• Support for Reyee Mesh technology • VPN networks: IPsec VPN, Open VPN, L2TP VPN, PPTP VPN, etc. • Static / dynamic routing • WAN : PPPoE, PPTP, L2TP • DHCP client/server support • Access Control List - ACL package filtering based on source and destination IP addresses • Rate limit • Load balance • NAT • Reboot schedule • View topology and network status • RESET button
Power supply:	12 V DC / 1.5 A (power adapter included)
Power consumption:	≤ 15 W
Operation temp:	0 °C ... 40 °C
Permissible relative humidity:	10 % ... 90 % (non-condensing)
Weight:	0.29 kg
Dimensions:	119 x 119 x 29 mm
Manufacturer / Brand:	RUIJIE / REYEE
Guarantee:	2 years

PRESENTATION



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
 POL; 60-713 Poznań; Graniczna 10
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Connectors:





In the kit:



PACKAGE

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

