





	AC POWER SUPPLY ADAPTER AWT-468 PULSAR	AC POWER SUPPLY ADAPTER AWT-682 PULSAR	AC POWER SUPPLY ADAPTER TR-40VA/NORATEL SATEL	AC POWER SUPPLY ADAPTER TR-60VA/NORATEL SATEL
				
	21.35 EUR 21.35 EUR	27.90 EUR 27.90 EUR	27.80 EUR 27.80 EUR	34.35 EUR 34.35 EUR
Adapter type	Transforming	Transforming	Transforming	Transforming
Power voltage	230 V AC	230 V AC	230 ... 250 V AC	230 V AC
Frequency range	50 Hz	50 Hz	47 ... 63 Hz	47 ... 63 Hz
Output voltage	<ul style="list-style-type: none"> • 16 V AC, • 18 V AC 	<ul style="list-style-type: none"> • 18 V AC, • 20 V AC 	16 V, 18 V AC	18 V, 20 V AC
EN norm	EN61558-2-6	EN61558-2-6
Test voltage between PRI/SEC	AC 4kV RMS	AC 4kV RMS
Maximal load	<ul style="list-style-type: none"> • 2.2 A @ 16 V AC, • 2 A @ 18 V AC 	<ul style="list-style-type: none"> • 3.3 A @ 18 V AC, • 3 A @ 20 V AC 	2.22 A	3 A
Safety class	II	II
Environment class	II	II
Isolation class	B (130°C)	B (130°C)
"Index of Protection"	IP43	IP43	IP44	IP43
Output power	40 VA	60 VA	40 VA	60 VA
Application	<ul style="list-style-type: none"> • to alarm systems powering • to automatic systems • to low-voltage light installation powering 	<ul style="list-style-type: none"> • to alarm systems powering • to automatic systems • to low-voltage light installation powering 	<ul style="list-style-type: none"> • to alarm systems powering • to automatic systems • to low-voltage light installation powering 	<ul style="list-style-type: none"> • to alarm systems powering • to automatic systems • to low-voltage light installation powering
Output	2 pcs	2 pcs	2 pcs	2 pcs
Weight	1.29 kg	1.29 kg	1.01 kg	1.23 kg
Dimensions	124 x 75 x 65 mm	124 x 75 x 65 mm	124 x 72 x 67 mm	124 x 72 x 67 mm
Manufacturer / Brand	PULSAR	PULSAR	SATEL	SATEL
Guarantee	2 years	2 years	2 years	2 years