










	ANGLE TYPE BRACKET D5-B VIDEOS	ANGLE TYPE BRACKET D5-S VIDEOS	SWITCHING ADAPTER WITH SEPARATOR M- SEP/HDR-30-24 VIDEOS	SWITCHING ADAPTER PL5-1116 VIDEOS	DESK STAND P100 VIDEOS	UNIVERSAL CONTROL MODULE 24V B5 VIDEOS	MULTIFUNCTIONAL MODULE M-3F VIDEOS	LAN COMMUNICATION MODULE M-LAN VIDEOS	MODULE M-SM4 VIDEOS DUO
									
	15.63 USD 15.63 USD	15.63 USD 15.63 USD	49.49 USD 49.49 USD	12.50 USD 12.50 USD	18.23 USD 18.23 USD	28.66 USD 28.66 USD	83.35 USD 83.35 USD	119.81 USD 119.81 USD	31.78 USD 31.78 USD
Support	VIDOS DUO 2-wire Video Doorphones	...	VIDOS DUO 2-wire Video Doorphones
Material	Aluminum - powder painted	Aluminum - powder painted	Acrylic glass (plexiglass)
Number of relay outputs	1
Interface	2-wire	...	2-wire
Compatibility	VIDOS DUO	VIDOS DUO - G24	...
Application	S6 product series	S6 product series	Internal VIDEOS video doorphone panels
Adapter type	Switching	Switching
Operation state indication	LED indication	...	LED indication
Color	Black	Silver	Transparent
Assembly	DIN, TS-35 rail mounting	DIN, TS-35 rail mounting	DIN, TS-35 rail mounting
Relay maximal load	2 A / 24 V DC
Power voltage	85 ... 264 V AC	110 V ... 240 V AC
Output voltage	24 V DC	11 ... 16 V DC
Output	1 x NO/NC
Output voltage adjustment	21.6 ... 29 V	✓
External dimensions	128 x 48 x 28 mm	128 x 48 x 28 mm	240 x 136 x 111 mm
Maximal load	1.5 A	950 mA
Output power	36 W	15 W
Number of outputs	4 pcs	1 pcs
Main features	<ul style="list-style-type: none"> • Wiring - 2 wires without polarity • Electric lock supply: 12V DC / max. 300mA • DIP SWITCH for configuration and addressing • Operation status LED indicator • Output for the additional lock release button or lighting control button • Possibility to mount on a wall, or on the DIN TS-35 rail 	<ul style="list-style-type: none"> • The maximum number of modules in the system : 199 • The maximum number of gate stations in the system : 199 • The maximum number of subscribers in the system : 6368 • Possibility to mount on a wall, or on the DIN TS-35 rail
Housing type	DIN	DIN
Vibration resistance	✓
Protections	<ul style="list-style-type: none"> • Short-circuit • Overload • Overvoltage
Main features	<ul style="list-style-type: none"> • Repeater - Increasing the transmission range up to 300m • Router - Connecting more users : max. 32 / M-3F Module, max. 8 max. 8 modules - max. 256 users (total) • Gateway - Possibility to connect a MASTER gate station
Power supply	24 V DC	24 V DC	24 V DC	24 V DC
Power consumption	<ul style="list-style-type: none"> • 0.32 W (Standby mode) • 2.7 W (operation)
Weight	0.1 kg	0.1 kg	0.33 kg	0.06 kg	0.232 kg	0.13 kg	0.2 kg	0.18 kg	0.13 kg
Dimensions	70 x 98 x 59 mm	18 x 90 x 58 mm	...	89 x 71 x 45 mm	90 x 72 x 60 mm	90 x 72 x 61 mm	89 x 72 x 45 mm
Operation temp	-10 °C ... 50 °C	-10 ... 55 °C	...	-10 ... 55 °C
Manufacturer / Brand	VIDOS	VIDOS	VIDOS	VIDOS	VIDOS	VIDOS	VIDOS	VIDOS	VIDOS DUO
Guarantee	3 years	3 years	2 years	3 years	3 years	3 years	3 years	3 years	3 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00