

Code: 24V/1A/GPV

SWITCHING ADAPTER 24V/1A/GPV

Net: 31.35 PLN Gross: 31.35 PLN

Hermetic power supply in a plastic housing.

Attention! If the power adaptor is using for continuous work (24H) the rated current of the adaptor should be less than 80% of the maximal current.

Please pay attention for proper cooling conditions of the power adaptor during work!



SPECIFICATION

Adapter type:	Switching
Power voltage:	90 ... 264 V AC
Frequency range:	47 ... 63 Hz
Output voltage:	24 V DC
Output voltage tolerance:	± 3 %
Maximal load:	1 A
Output power:	20 W
Efficiency:	84 %
Number of outputs:	1 pcs
Protections:	<ul style="list-style-type: none">• Overload• Short-circuit• Overvoltage• Overheat
Main features:	<ul style="list-style-type: none">• Protection class : II• Box casing designed to wall mounting
Housing type:	Plastic, Waterproof
"Index of Protection":	IP67
Operation temp:	-30 °C ... 70 °C
Weight:	0.18 kg
Dimensions:	140 x 32 x 25 mm
Guarantee:	3 years

PRESENTATION



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Top view:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------