

Code: PFM350-360

UPS PFM350-360 600 VA DAHUA

Net: 122.02 EUR Gross: 122.02 EUR

The PFM350-360 UPS is a professional device used to maintain the operation of the components connected to it.



SPECIFICATION

Nominal power:	360 W
Apparent Power:	600 VA
Input voltage:	140 V ... 290 V AC
Input frequency:	50 / 60 Hz
Output voltage:	220 ... 240 V AC \pm 10 % (Approximated Sine Wave)
Output frequency:	50 / 60 Hz \pm 1 Hz
Transfer time:	2 ... 6 ms
Charging time (recover to 90% capacity):	4 ... 6 hours (typical)
Battery:	1 pcs - 12V/7Ah
Number of outputs:	2 pcs CEE 7/3 (Schuko)
Protections:	<ul style="list-style-type: none">• Glass Fuse• Overload protection• Overcharge protection• Discharge
Operation state indication:	<ul style="list-style-type: none">• LED diodes,• Sound signaling
Main features:	<ul style="list-style-type: none">• Wide input voltage range• Automatic Voltage Regulator (AVR)• Battery charging at power-off mode• COLD START: - Cold start of the power adapter• Small dimensions
Application:	<ul style="list-style-type: none">• Surveillance Systems• data storage centers• network, servers, workstations• Industrial Equipment
Housing type:	Tower

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Operation temp. / Relative humidity:	0 °C ... 40 °C / 0 ... 90 %
Weight:	4.13 kg
Dimensions:	279 x 101 x 142 mm
Manufacturer / Brand:	DAHUA
Guarantee:	3 years

PRESENTATION

Front panel:



Rear view:



Connectors:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------