

Code: AT-UPS650BK-LED

## UPS AT-UPS650BK-LED 650 VA EAST

Net: 303.78 PLN Gross: 303.78 PLN

The AT-UPS650BK-LED UPS has been equipped with a number of advanced technologies ensuring active monitoring of the power supply network. The device works with power supply adapters having Active Power Factor Correction (APFC).



### SPECIFICATION

|                                          |                                                                                                                                                  |
|------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|
| Nominal power:                           | 390 W                                                                                                                                            |
| Apparent Power:                          | 650 VA                                                                                                                                           |
| Input voltage:                           | 173 V ... 287 V AC                                                                                                                               |
| Input frequency:                         | 50 / 60 Hz (auto detection)                                                                                                                      |
| Output voltage:                          | 230 V AC $\pm$ 10 % (Approximated Sine Wave)                                                                                                     |
| Output frequency:                        | 50 / 60 Hz $\pm$ 1 %                                                                                                                             |
| Transfer time:                           | 2 ... 7 ms (typical), max. 10 ms                                                                                                                 |
| Charging time (recover to 90% capacity): | 8 hours                                                                                                                                          |
| Battery:                                 | 1 pcs - 12V/7Ah                                                                                                                                  |
| Estimated battery operation time:        | <ul style="list-style-type: none"><li>• 19 minutes @ 100 W,</li><li>• 6 minutes @ 200 W,</li><li>• 2 minutes @ 300 W</li></ul>                   |
| Number of outputs:                       | 2 pcs CEE 7/3 (Schuko)                                                                                                                           |
| Protections:                             | <ul style="list-style-type: none"><li>• Glass Fuse</li><li>• Overvoltage</li><li>• Overload protection</li><li>• Overcharge protection</li></ul> |
| Operation state indication:              | <ul style="list-style-type: none"><li>• LED diodes,</li><li>• Sound signaling</li></ul>                                                          |

|                                      |                                                                                                                                                                                                                      |
|--------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Main features:                       | <ul style="list-style-type: none"> <li>• Auto restart while AC is recovering</li> <li>• Automatic Voltage Regulator (AVR)</li> <li>• Compatible with power generators</li> <li>• Built-in EMI, RFI filter</li> </ul> |
| Application:                         | <ul style="list-style-type: none"> <li>• Surveillance Systems</li> <li>• data storage centers</li> <li>• network, servers, workstations</li> <li>• Industrial Equipment</li> </ul>                                   |
| Housing type:                        | Tower                                                                                                                                                                                                                |
| Operation temp. / Relative humidity: | 0 °C ... 40 °C / 20 ... 90 %                                                                                                                                                                                         |
| Weight:                              | 4.2 kg                                                                                                                                                                                                               |
| Dimensions:                          | 300 x 100 x 140 mm                                                                                                                                                                                                   |
| Manufacturer / Brand:                | EAST                                                                                                                                                                                                                 |
| Guarantee:                           | 2 years                                                                                                                                                                                                              |

## PRESENTATION

Front view:



Rear view:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
 POL; 60-713 Poznań; Graniczna 10  
 e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60



#### PACKAGE

|                                  |                    |
|----------------------------------|--------------------|
| Dimensions (L x W x H): 0x0x0 mm | Gross Weight: 0 kg |
|----------------------------------|--------------------|