

Code: TM-LI-OFFICEPRO-600-F2

## UPS **TM-LI-OFFICEPRO-600-F2** 600 VA IPS

Net: **251.16 PLN** Gross: **251.16 PLN**

The TM-LI-OFFICEPRO-600-F2 UPS is intended for office equipment, telecommunications systems and CCTV security systems. The UPS ensures stable operation of the devices connected to it in the event of a power outage.

The TM-LI-OFFICEPRO-600-F2 model has a built-in AGM battery.



### SPECIFICATION

Power adapter type:	Line-interactive
Nominal power:	360 W
Apparent Power:	600 VA
Input voltage:	162 V ... 295 V AC
Input frequency:	50 / 60 Hz (auto detection)
Output voltage:	230 V AC $\pm$ 5 % (Approximated Sine Wave)
Output frequency:	50 / 60 Hz $\pm$ 1 %
Power factor:	0.6
Voltage adjustment:	—
Frequency adjustment:	—
Transfer time:	2 ... 7 ms (typical) max. 10 ms
Charging time (recover to 90% capacity):	5 ... 8 hours
Battery:	1 pcs - 12V/7Ah AGM
Estimated battery operation time:	<ul style="list-style-type: none"><li>• 2 minutes @ 100 %,</li><li>• 5 minutes @ 75 %,</li><li>• 8 minutes @ 50 %,</li><li>• 10 minutes @ 25 %</li></ul>
Number of outputs:	2 pcs CEE 7/3 (Schuko)
Management software:	UPSmart (Windows 98/2000/2003/XP/Vista/2008/7/8/10)

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

Protections:	<ul style="list-style-type: none"> <li>• Glass Fuse</li> <li>• Overload</li> <li>• Short-circuit</li> <li>• Overvoltage</li> <li>• Temperature</li> <li>• Overcharge</li> <li>• Protection against deep discharge of the battery</li> <li>• Telephone line filter</li> </ul>
Operation state indication:	<ul style="list-style-type: none"> <li>• LCD display: operation mode, battery charging level, in/out voltage level, Work load,</li> <li>• Sound signaling</li> </ul>
Main features:	<ul style="list-style-type: none"> <li>• Microprocessor control system</li> <li>• UPS auto diagnostic system</li> <li>• Auto restart while AC is recovering</li> <li>• COLD START: - Cold start of the power adapter</li> <li>• Automatic battery charging in OFF mode</li> <li>• Built-in AVR voltage stabilization system</li> <li>• Built-in EMI, RFI filter</li> <li>• 2 x RJ-11 - Input / Output</li> <li>• Communication interface - Port USB</li> <li>• USB A / USB B cable included</li> </ul>
Application:	<ul style="list-style-type: none"> <li>• to Home &amp; Small Office applications</li> <li>• Telecommuniacion</li> <li>• CCTV - Surveillance Systems</li> </ul>
Housing type:	Tower
Operation temp. / Relative humidity:	0 °C ... 40 °C / 20 ... 90 %
Weight:	4.37 kg
Dimensions:	305 x 90 x 165 mm
Manufacturer / Brand:	IPS
Guarantee:	2 years

## PRESENTATION

Front view:



Rear view:

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
 POL; 60-713 Poznań; Graniczna 10  
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



In the kit:



## PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------