

Code: VFD-600/FR

## UPS VFD-600/FR 600 VA

Net: 57.05 EUR Gross: 57.05 EUR

The VFD-600/FR UPS is a professional device used to maintain the operation of the components connected to it. The device has a small casing, economical design and automatic start in the absence of mains power.



### SPECIFICATION

Nominal power:	360 W
Apparent Power:	600 VA
Input voltage:	180 ... 270 V AC
Input frequency:	50 / 60 Hz (auto detection)
Output voltage:	230 V AC (Approximated Sine Wave)
Output frequency:	50 / 60 Hz $\pm$ 1 %
Charging time (recover to 90% capacity):	to 8 hours
Estimated battery operation time:	<ul style="list-style-type: none"><li>• 7 minutes - 50% load</li><li>• 0.5 minutes - 100% load</li></ul>
Battery:	12 V / 7 Ah
Number of outputs:	2 x "E" PL socket
Transfer time:	2 ... 6 ms
Operation state indication:	LEDs and buzzer
Protections:	<ul style="list-style-type: none"><li>• Overcharge protection</li><li>• discharge protection</li><li>• short-circuit protection</li><li>• thermal protection</li></ul>
Main features:	<ul style="list-style-type: none"><li>• Excellent microprocessor control guarantees high reliability</li><li>• Auto restart while AC is recovering</li><li>• "Cold Start" function</li><li>• Possibility to mount to the wall</li></ul>
Housing type:	Tower / Desktop
Dimensions:	228 x 206 x 83 mm
Weight:	2.91 kg
Manufacturer / Brand:	PowerWalker
Guarantee:	2 years

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

## PRESENTATION

Device connectors:



In the kit:



## PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------