

Code: TM-LI-OFFICEPRO-1200-F4

UPS TM-LI-OFFICEPRO-1200-F4 1200 VA IPS

Net: 446.16 PLN Gross: 446.16 PLN

The TM-LI-OFFICEPRO-1200-F4 UPS is intended for office equipment, telecommunications systems and CCTV security systems. The UPS ensures stable operation of the devices connected to it in the event of a power outage.

The TM-LI-OFFICEPRO-1200-F4 model has a built-in AGM batteries.



SPECIFICATION

Power adapter type:	Line-interactive
Nominal power:	720 W
Apparent Power:	1200 VA
Input voltage:	162 V ... 295 V AC
Input frequency:	50 / 60 Hz (auto detection)
Output voltage:	230 V AC \pm 5 % (Approximated Sine Wave)
Output frequency:	50 / 60 Hz \pm 1 %
Power factor:	0.6
Voltage adjustment:	—
Frequency adjustment:	—
Transfer time:	2 ... 7 ms (typical) max. 10 ms
Charging time (recover to 90% capacity):	5 ... 8 hours
Battery:	2 pcs - 12V/7Ah AGM
Estimated battery operation time:	<ul style="list-style-type: none">• 2 minutes @ 100 %• 5 minutes @ 75 %• 8 minutes @ 50 %• 10 minutes @ 25 %
Number of outputs:	4 pcs CEE 7/3 (Schuko)
Management software:	UPSmart (Windows 98/2000/2003/XP/Vista/2008/7/8/10)

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Protections:	<ul style="list-style-type: none"> • Glass Fuse • Overload • Short-circuit • Overvoltage • Temperature • Overcharge • Protection against deep discharge of the battery • Telephone line filter
Operation state indication:	<ul style="list-style-type: none"> • LCD display: operation mode, battery charging level, in/out voltage level, Work load, • Sound signaling
Main features:	<ul style="list-style-type: none"> • Microprocessor control system • UPS auto diagnostic system • Auto restart while AC is recovering • COLD START: - Cold start of the power adapter • Automatic battery charging in OFF mode • Built-in AVR voltage stabilization system • Built-in EMI, RFI filter • 2 x RJ-11 - Input / Output • Communication interface - Port USB • USB A / USB B cable included
Application:	<ul style="list-style-type: none"> • to Home & Small Office applications • Telecommuniacion • CCTV - Surveillance Systems
Housing type:	Tower
Operation temp. / Relative humidity:	0 °C ... 40 °C / 20 ... 90 %
Weight:	8.68 kg
Dimensions:	320 x 115 x 220 mm
Manufacturer / Brand:	IPS
Guarantee:	2 years

PRESENTATION

Front view:



Rear view:

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
 POL; 60-713 Poznań; Graniczna 10
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------