

Code: VI-2000/LCD

## UPS VI-2000/LCD 2000 VA

Net: 1 153.79 PLN Gross: 1 153.79 PLN

The VI-2000/LCD UPS is a professional device used to maintain the operation of the components connected to it. Additionally protects the connected equipment against overvoltages.



### SPECIFICATION

|                                          |                                                                                                                                                                                                                                                                                                                                                                                                                                |
|------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Nominal power:                           | 1200 W                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Apparent Power:                          | 2000 VA                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Input voltage:                           | 162 ... 290 V AC                                                                                                                                                                                                                                                                                                                                                                                                               |
| Output voltage:                          | 230 V AC (Approximated Sine Wave)                                                                                                                                                                                                                                                                                                                                                                                              |
| Output frequency:                        | 50 / 60 Hz $\pm$ 1 %                                                                                                                                                                                                                                                                                                                                                                                                           |
| Charging time (recover to 90% capacity): | 4 ... 6 hours                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Estimated battery operation time:        | 20 minutes                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Battery:                                 | 2 x 12V/9Ah                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Number of outputs:                       | 2 pcs                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Number of inputs:                        | 2 pcs                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Transfer time:                           | 2 ... 6 ms (max. 10 ms)                                                                                                                                                                                                                                                                                                                                                                                                        |
| Management software:                     | ViewPower (Polish version - Windows 98/2000/XP/Vista/7/8, MAC, Linux, FreeBSD, Solaris)                                                                                                                                                                                                                                                                                                                                        |
| Additional protection:                   | RJ11, RJ45                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Protections:                             | <ul style="list-style-type: none"><li>• Overcharge</li><li>• Discharge</li><li>• Short-circuit</li></ul>                                                                                                                                                                                                                                                                                                                       |
| Main features:                           | <ul style="list-style-type: none"><li>• Auto restart while AC is recovering</li><li>• Short-time charging</li><li>• Excellent microprocessor control guarantees high reliability</li><li>• Built-in AVR voltage stabilization system</li><li>• Battery charging at power-off mode</li><li>• "Cold Start" function</li><li>• USB interface</li><li>• Energy Saving function (possibility to deactivate from software)</li></ul> |
| Application:                             | to Home & Small Office applications                                                                                                                                                                                                                                                                                                                                                                                            |
| Operation state indication:              | LCD display: operation mode, battery charging level, in/out voltage level                                                                                                                                                                                                                                                                                                                                                      |
| Housing type:                            | Tower                                                                                                                                                                                                                                                                                                                                                                                                                          |

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

|             |                    |
|-------------|--------------------|
| Dimensions: | 397 x 147 x 205 mm |
| Weight:     | 11.92 kg           |
| Guarantee:  | 2 years            |

PRESENTATION

Device connectors:



Example of displayed information:



In the kit:



PACKAGE



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

|                                  |                    |
|----------------------------------|--------------------|
| Dimensions (L x W x H): 0x0x0 mm | Gross Weight: 0 kg |
|----------------------------------|--------------------|

