

Code: GRAPHITE-VARNISH

GRAPHITE VARNISH **GRAPHITE-VARNISH 2 X VIAL 1.5 ml AG** TERMOPASTY

Net: **11.82 PLN** Gross: **11.82 PLN**

The GRAPHITE-VARNISH conductive graphite varnish can be used to repair of graphite-coated boards in electronic devices (calculators, remote controls), filling losses in graphite coatings, or repair damaged paths on printed circuit boards. The product has the consistency of a thick liquid, which greatly facilitates application even when great precision is required.

The GRAPHITE-VARNISH varnish is a light-sensitive material and requires curing under light after application. The manufacturer recommends curing by placing a freshly applied layer of product at a distance of about 15 cm from a 100 W light bulb for about 90 minutes.

A dedicated solvent is added to the varnish, allowing both to restore the original consistency of the product if it thickens excessively and to make minor adjustments during and after application.



SPECIFICATION

Package:	2 x Vial 1.5 ml (varnish + solvent)
Application:	<ul style="list-style-type: none">• Repair and renovation of graphite coatings in electronic devices,• Reconstruction of paths in printed circuit boards
Main features:	<ul style="list-style-type: none">• Density : 1.2 g/cm³ @ 20 °C,• Viscosity : 15 ... 50 Pa·s @ 20 °C• Good electrochemical corrosion protection on metal• Photosensitive varnish• Dedicated solvent (ethyl acetate) included
Color:	Black
Manufacturer / Brand:	AG TERMOPASTY

PRESENTATION

Package:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------