PROFFESSIONAL 2-COMPONENT ADHESIVE **K2-PLASTIPOX/25G** TUBE 25 g K2

Net: 18.33 PLN Gross: 18.33 PLN

Epoxy adhesive for professional bonding of all kinds of surfaces, especially plastic ones. Permanently bonds most combinations of dissimilar materials such as plastics, metals, ceramics, porcelain, fiberglass, glass, PVC, leather, wood and many other materials.

The adhesive has high resistance to impact, water, gasoline, kerosene and oils. Perfectly fills gaps.

The K2-PLASTIPOX/25G is offered in the form of adhesive in a syringe. The innovative syringe applicator guarantees simple use and optimal dosing of both components at the same time. The closed syringe protects the product from drying out, thanks to which the adhesive retains its properties long after opening and does not dry out.

Attention! The adhesive does not bond with polyethylene (PE) and polypropylene (PP) plastics.



SPECIFICATION

Package:	Tube 25 g
Color:	White
Main features:	Type of glue - epoxy adhesive Application: Plastic, PVC, ABS, Metal, Stainless steel, Glass, Ceramics, Porcelain, Fiberglass, Natural Leather, Wood, and others, Bond strength: 305 kg/cm², Glue bonding time: 7 minutes - initial, 2 h - Bond strength 75 %, 24 h - Full hardening Ability to move the glued object after 15 minutes The adhesive has high resistance to impact, water, gasoline, kerosene and oils. Maximum thickness of the gaps to be filled: 10 mm Temperature strength of fully cured adhesive bond: -55 °C 120 °C
Dimensions:	182 x 40 x 37 mm
Manufacturer / Brand:	K2

PRESENTATION

2024-05-24



Package:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm Gross Weight: 0 kg

2024-05-24